

This document was generated on 12/10/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	1731090340		
Status:	Active		3.0
Overview:	FCT D-Sub Connect		
Description:		ity D-Sub Connector, Male, Right-Angle, Surface Mount, 3.70mr Mating Cycles, Diecast Bracket, 15 Circuits	
	Contact Height, 500	Maling Cycles, Diecast Brackel, 15 Circuits	ANTER SCA
Desumenter			
Documents:		Del 19 Cartificate et Compliance (PDE)	
Brochure (PDF)		RoHS Certificate of Compliance (PDF)	
General			Series image - Reference only
Product Family		D-Sub Products	Series image - Reference only
Series		173109	
IP Rating		IP20	<u>EU ELV</u>
Overview		FCT D-Sub Connectors	Not Relevant
Product Category		D-Sub Connector	Ell Delle Chine Delle
Product Name		FCT Products	EU RoHS China RoHS
Туре		Standard Density	Compliant REACH SVHC
UPC		191128115452	
Physical			Not Reviewed
Physical		45	Halogen-Free
Circuits (Loaded)		15	<u>Status</u>
Circuits (maximum)		15 Notural	Not Reviewed
Color - Resin		Natural	For more information, please visit <u>Contact US</u>
Durability (mating cy	cies max)	500 Mole	China ROHS Green Image
Gender Material Contact			ELV Not Relevant
Material - Contact		Copper Alloy	RoHS Phthalates Not Contained
Material - Resin		PBT	Nono Finnaiales Not Contained
Material - Shell		Steel	
Net Weight		13.600/g	
Number of Rows		2	Search Parts in this Series
Orientation		Right-Angle	<u>173109</u> Series
PC Tail Length		3.70mm	
PCB Locator		Yes	Mates With
PCB Retention		Yes	FCT Standard-Density D-Sub, Size 2, 15
PCB Thickness - Recommended		1.60mm	Position, Socket
Packaging Type		Embossed Tape on Reel	
Panel Mount	J	Rear Thread In	
Panel Mount Method		Thread-In	
Pitch - Mating Interfa		2.84mm	
Pitch - Termination I	menace	3.40mm Cold over Belledium Niekel	
Plating - Contact		Gold over Palladium Nickel	
Plating - Shell	Dort	Nickel	
Polarized to Mating	Part	Yes	
Polarized to PCB		Yes	
Ports		l Voc	
Shielded	natible (CMC)	Yes	
Surface Mount Com		Yes	
Temperature Range	- Operating	-55° to +150°C	
Termination Style	a a f	Surface Mount	
Waterproof / Dustpro		No	
Waterproof / Dustpro	от туре	IP20	
Electrical			
Current - Maximum	per Contact	5.0A	

Material Info

Engineering Number

FSLT15P101G1-3752

This document was generated on 12/10/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 56F711-015
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104
 012-0467-000
 012-9507-034
 012

 9507-114
 020745-0008
 609-25P
 CT2-14S-2PCA34
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC
 CT6-14S-2SC
 CT6E14SA7SC

 M83513/01-FC
 M83723/76W24619 L/C
 M85049/48-3-2F
 6STD09PCM99B70X
 6STD09SCM99B30X
 6STD09SCT99S40X

 6STD15PCT99S40X
 6STD15SCM99B30X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN
 747552-3
 MD1-21PS

 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076
 MIKQ7-7PH077
 MIKQ7

 7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16-GROM-SEALING
 GDA15P

 GDAY15PB
 980-0000-170
 980-0000-171
 980-0000-171
 980-0000-171