

## This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Dert Number				
Part Number:	<u>1731090704</u>			
Status:	Active		88888888888888888888888888888888888888	
Overview:	FCT D-Sub Connecto	<u>rs</u>		
Description:	FCT Standard-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold over Nickel Phosphorus Plating, 500 Mating Cycles, 15 Circuits			
Documents:				
Datasheet (PDF)		RoHS Certificate of Compliance (PDF)		]
Brochure (PDF)				
General			Series image	- Reference only
Product Family		D-Sub Products		1
Series		173109	EU ELV	
IP Rating		IP20	Not Relevant	
Overview		FCT D-Sub Connectors		
Product Category		D-Sub Connector	EU RoHS	<u>China RoHS</u>
Product Name		FCT Products	Compliant with	
Туре		Standard Density	Exemption 6(c)	
UPC		191128904872	REACH SVHC	
010		191120304072	Not Reviewed	
Physical			Halogen-Free	
Circuits (Loaded)		15	Status	
Circuits (maximum)		15	Not Reviewed	
Color - Resin		White		, please visit <u>Contact US</u>
Durability (mating cycles max) 500			For more information,	, please visit <u>Contact 03</u>
Gender		Female	China ROHS	50 Image
Material - Contact		Copper Alloy	ELV	Not Relevant
Material - Resin		PBT	RoHS Phthalates	Not Contained
Material - Shell		Steel		Not Contained
Net Weight Number of Rows		8.200/g		
		2 Staright	Search Parts in this Series	
Orientation		Straight	<u>173109</u> Series	
PC Tail Length		10.30mm		
PCB Locator		Yes	Mates With	
PCB Retention		Yes	FCT Standard-Density D-Sub, Size 2, 15	
PCB Thickness - Recommended		1.60mm	Position, Plug	ony _ cas, cc _, .c
Packaging Type		Carton		
Panel Mount		Rear		
Panel Mount Method		Flange		
Pitch - Mating Interfa		2.84mm		
Pitch - Termination Ir	nterface	2.84mm		
Plating - Contact		Gold over Nickel Phosphorus		
Plating - Shell	_	Tin		
Polarized to Mating F	Part	Yes		
Polarized to PCB		Yes		
Ports		1		
Shielded		Yes		
Temperature Range	<ul> <li>Operating</li> </ul>	-55° to +125°C		
Termination Style		Through Hole		
Waterproof / Dustpro		No		
Waterproof / Dustpro	of Type	IP20		
Electrical				
Current - Maximum p	per Contact	7.5A		
Material Info Engineering Number		F15S1G1A		

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

56F706-005-LI 56F711-015 LV242999-142T12 015-0341-000 015-0372-005 015-0372-008 015-8755-001 020419-0104 012-0467-000 012-9507-034 012-9507-114 020745-0008 609-25P CT2-14S-2PCA34 CT2-18-11PCAU CT6-10SL-3SC CT6-10SL-4SC CT6-14S-2SC CT6E14SA7SC CT6N10SL-4SSA34 M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X 6STD15PCT99S40X 6STD15SCT99S40X 6STF09PCM05B70X 7-135760-9 MC11E-10-6SN 747552-3 MD1-21PS MDM-15SCBRM7-F222 MDM96517-699 MDM96521-744 MDVB1-21SL1 MIK0-1-7SH003 MIKQ6-7SH076 MIKQ7-7PH077 MIKQ7-7PH11 MIKQ7-7PH32 MJSV-28SL61 MKJ4A1F14-55S 8-135760-3 8STD09PCM99B30X PG-KV/PV-16-GROM-SEALING GDA15P GDAY15PB 980-0000-170