

## This document was generated on 07/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	1731091904			
Status:	Active			
Overview: Description:	FCT D-Sub Connectors FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold over Nickel Phosphorus Plating, 500 Mating Cycles, Plastic Bracket with Snap-in Grounding Bracket and Clinch Nut, 25 Circuits		$ \begin{array}{c}                                     $	
Decumenter				
Documents: Datasheet (PDF)		RoHS Certificate of Compliance (PDF)		
Brochure (PDF)			- Series image - Reference only	
General				
Product Family		D-Sub Products	EU ELV	
Series		173109	Not Relevant	
IP Rating		IP20	NOT Relevant	
e e e e e e e e e e e e e e e e e e e			EU RoHS China RoHS	
Overview		FCT D-Sub Connectors		
Product Category		D-Sub Connector	Not Reviewed	
Product Name		FCT Products	REACH SVHC	
Туре		Standard Density	Not Reviewed	
UPC		191130143573	Halogen-Free	
Physical			Status Not Reviewed	
Circuits (Loaded)		25	For more information, please visit Contact US	
Circuits (maximum)		25	For more information, please visit <u>contact 05</u>	
			China ROHS Not Reviewed	
Color - Resin		White	ELV Not Relevant	
Durability (mating cycles max)		500		
Gender		Female	RoHS Phthalates Not Reviewed	
Material - Contact		Copper Alloy		
Material - Resin		PBT		
Material - Shell		Steel	Oceand, Dente in this Contact	
Net Weight		12.000/g	Search Parts in this Series	
Number of Rows		2	<u>173109</u> Series	
Orientation		—		
		Right-Angle	Mates With	
PC Tail Length		11.10mm	FCT Standard-Density D-Sub, Size 3, 25	
PCB Locator		Yes		
PCB Retention		Yes	Position, Plug	
PCB Thickness - Recommended		1.60mm		
Packaging Type		Carton		
Panel Mount		Rear		
Panel Mount Method	4	Thread-In		
Pitch - Mating Interface		2.84mm		
Pitch - Termination Interface				
	menace	2.54mm		
Plating - Contact		Gold over Nickel Phosphorus		
Plating - Shell		Tin		
Polarized to Mating I	Part	Yes		
Polarized to PCB		Yes		
Ports		1		
Shielded		Yes		
Temperature Range	- Operating	-55° to +125°C		
	operating			
Termination Style	<b>f</b>	Through Hole		
Waterproof / Dustpro		No		
Waterproof / Dustpro	oof Type	IP20		
Electrical				
Current - Maximum	per Contact	7.5A		
Material Info				

## This document was generated on 07/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 56F711-015
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104
 012-0467-000
 012-9507-034
 012 

 9507-114
 020745-0008
 609-25P
 CT2-14S-2PCA34
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC
 CT6-14S-2SC
 CT6E14SA7SC

 M83513/01-FC
 M83723/76W24619 L/C
 M85049/48-3-2F
 6STD09PCM99B70X
 6STD09SCM99B30X
 6STD09SCT99S40X

 6STD15PCT99S40X
 6STD15SCM99B30X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN
 747552-3
 MD1-21PS

 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076
 MIKQ7-7PH077
 MIKQ7 

 7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16-GROM-SEALING
 GDA15P

 GDAY15PB
 980-0000-170
 980-0000-171
 980-0000-171
 980-0000-171