

## This document was generated on 04/10/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:       1731091961         Status:       Active         Overview:       FCT Solutionation         Pering: 200 Matring Cycles, Pleate Bracket with Snap-in Grounding Bracket and Clinth Nul. 28 Circuits       Solutionation Comparison         Documents:       Bashbet:/PDF       BathS Cartificate of Compliance (PDF)         Series       173109       Pleate Cartificate of Compliance (PDF)         Overview       FCT D-Sub Connectors       China RoHS         Product Category       D-Sub Connectors       China RoHS         Product Imating       Status       Ontal Reviewed         Chronis (mating cycles max)       200       Concertains       Not Reviewed         Outcoments:       Concertains       Not Reviewed       Encliption						
Overview Bescription:         CTLD Sub Connector: FCT Standard Density D-Sub Connector: Male, Right-Angle, PCB Through Hole, Gold Nut, 25 Circuits         Outcometer: Nut, 25 Circuits           Decements: Basebarour (PDF) Basebarour (PDF) Series         RoHS Centificate of Compliance (PDF)         Series image - Reference only           Concents: Basebarour (PDF) Series         Polyton         Chained Density D-Sub Products         Series image - Reference only           Series         173109         P20         Not Reviewed         EU RoHS           Product Category         D-Sub Connectors         Not Reviewed         EU RoHS           Product Category         D-Sub Connectors         Not Reviewed         EU ROHS           Product Category         D-Sub Connectors         Not Reviewed         Not Reviewed           Product Category         D-Sub Connectors         Not Reviewed         Not Reviewed           Product Category         D-Sub Connectors         Not Reviewed         Not Reviewed           Product Category         25         Circuits (Casterin)         Not Reviewed           Cater of Carted         Capper Ality         Not Reviewed         Not Reviewed           Material - Steel         Material - Steel         Not Reviewed         Steel           Orier resting         White         Steel         Not Reviewed         Steel <td>Part Number:</td> <td><u>1731091961</u></td> <td></td> <td></td> <td></td>	Part Number:	<u>1731091961</u>				
Overview     FCT D-Sub Connectors       Description:     FCT D-Sub Connectors       Pating, 200 Mating Cycles, Plastic Bracket with Snap-in Grounding Blacket and Clinch Nut, 25 Circuits       Decements:     RoHS Certificate of Compliance (PDF)       Bacchure (FDE)     RoHS Certificate of Compliance (PDF)       Series     172.109       IP Rating     D-Sub Products       Series     172.109       IP Rating     D-Sub Connectors       Product Category     Not Reviewed       Product Category     Portone       Reviewed     China RoHS       Orrentist (masinum)     Z5       Cortins (Loaded)     Z5       Creating (maring cycles max)     200       Orne Reviewed     China RoHS       Number of Rows     2       Orneating (maring cycles max)     200       Central (Loaded)     13000rg    <	Status:	Active				
Databaset (PDF)       ReHS Certificate of Compliance (PDF)         Bacchure (PDF)       Series Image - Reference only         Product Family       D-Sub Products         Series       173109         IP Rating       IP20         Overview       FCT D-Sub Connectors         Product Name       FCT D-Sub Connectors         Product Name       FCT Products         Type       Standard Density         UPC       191130524730         Physical       Circuits (Loaded)         Circuits (Loaded)       25         Corrusts (Loaded)       25         Corrusts (Loaded)       25         Corrusts (Loaded)       26         Corrusts (Loaded)       26         Corrusts (Loaded)       27         Carlor Fasin       White         Durability (mating cycles max)       200         Color Fasin       Steel         Natt Weight       18.000g         Nurt Weight       19.000g         Nurt Weight       19.000g         Nurt Keises - Recommended       160mm         PoEs Trails ength Thereact - Yes       Poet Harts in this Series         POE Trails ength Interface       2.54mm         Poet Retention       Yes </td <td></td> <td>FCT D-Sub Connectors FCT Standard-Density D-Sub Plating, 200 Mating Cycles, P</td> <td colspan="2"><u>CT D-Sub Connectors</u> CT Standard-Density D-Sub Connector, Male, Right-Angle, PCB Through Hole, Gold lating, 200 Mating Cycles, Plastic Bracket with Snap-in Grounding Bracket and Clinch</td> <td colspan="2"><math display="block"> \begin{array}{c}                                     </math></td>		FCT D-Sub Connectors FCT Standard-Density D-Sub Plating, 200 Mating Cycles, P	<u>CT D-Sub Connectors</u> CT Standard-Density D-Sub Connector, Male, Right-Angle, PCB Through Hole, Gold lating, 200 Mating Cycles, Plastic Bracket with Snap-in Grounding Bracket and Clinch		$ \begin{array}{c}                                     $	
General       Poduct Family       D-Sub Products         Product Family       D-Sub Products       FUE LV         IP Rating       IP20         Overview       FCT D-Sub Connectors         Product Category       D-Sub Connectors         Type       Standard Density         UPC       191100264730         Physical       Chronits (Loaded)         Circuits (Loaded)       25         Circuits (maximum)       25         Color - Resin       White         Durability (mating cycles max)       200         Gender       Material - Contact         Number of Rows       2         Ore Takesin       PBT         Material - Contact       Coppor Alloy         Material - Contact       Coppor Alloy         Material - Contact       Coppor Alloy         Number of Rows       2         Ore Takiton       Right-Angle         PC Tai Length       11.00mm         PGB Retention       Yes         Pae Mount Method       Thread-In         Panet Mount Method       Thread-In         Pitch - Temilation Interface       2.84mm         Plating - Shell       Tin         Polarized to Mating Ipart       Yes </td <td>Datasheet (PDF)</td> <td></td> <td>RoHS Certificate of Compliance (PDF)</td> <td>Series image</td> <td>- Reference only</td>	Datasheet (PDF)		RoHS Certificate of Compliance (PDF)	Series image	- Reference only	
Product Family     D-Sub Products     EU ELV       Series     173109     Not Relevant       IP Rating     IP20       Overview     FCT D-Sub Connectors     EU RoHS     China RoHS       Product Category     D-Sub Connector     REACH SVHC     Not Reviewed       Product Name     FCT Products     Not Reviewed     Not Reviewed       Type     Standard Density     Halogen-Free     Status       UPC     191130524730     Status     Not Reviewed       Circuits (Loaded)     25     Color - Resin     Not Reviewed       Circuits (Institution (uning cycles max)     200     China ROHS     Not Reviewed       Durability (ming cycles max)     200     China ROHS     Not Reviewed       Material - Contact     Copper Alloy     Not Reviewed     RoHS Phthalates     Not Reviewed       Material - Contact     Copper Alloy     Not Reviewed     RoHS Phthalates     Not Reviewed       Number of Rows     2     Colination     Yes     Search Parts in this Series     173102 Series       PCB Ratention     Yes     Yes     Postion Socket     Postion Socket     Postion Socket       PCB Ratention     Yes     Carton     Postion Socket     Postion Socket     Postion Socket       PCB Ratention     Yes     Postion Sock	General					
Packaging TypeCartonPanel MountRearPanel Mount MethodThread-InPitch - Mating Interface2.84mmPitch - Termination Interface2.54mmPlating - ContactGold over NickelPlating - ShellTinPolarized to Mating PartYesPolarized to PCBYesPorts1ShieldedYesTermination StyleThrough HoleWaterproof / DustproofNoWaterproof / Dustproof TypeIP20ElectricalCurrent - Maximum per ContactCurrent - Maximum per Contact7.5A	Series IP Rating Overview Product Category Product Name Type UPC <b>Physical</b> Circuits (Loaded) Circuits (maximum) Color - Resin Durability (mating cycl Gender Material - Contact Material - Contact Material - Resin Material - Shell Net Weight Number of Rows Orientation PC Tail Length PCB Locator PCB Retention		173109 IP20 FCT D-Sub Connectors D-Sub Connector FCT Products Standard Density 191130524730 25 25 White 200 Male Copper Alloy PBT Steel 18.000/g 2 Right-Angle 11.10mm Yes Yes	Not Relevant         EU RoHS         Not Reviewed         REACH SVHC         Not Reviewed         Halogen-Free         Status         Not Reviewed         For more information         China ROHS         ELV         RoHS Phthalates         Search Parts in the 173109 Series         Mates With         FCT Standard-Deated	n, please visit <u>Contact US</u> Not Reviewed Not Relevant Not Reviewed	
Current - Maximum per Contact 7.5A	Packaging Type Panel Mount Panel Mount Method Pitch - Mating Interfac Pitch - Termination Int Plating - Contact Plating - Shell Polarized to Mating Pa Polarized to PCB Ports Shielded Temperature Range - Termination Style Waterproof / Dustproot	e terface art Operating of	Carton Rear Thread-In 2.84mm 2.54mm Gold over Nickel Tin Yes Yes 1 Yes -55° to +125°C Through Hole No			
		er Contact	7.5A			
	Material Info		-			

## This document was generated on 04/10/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2469 173109-2436 173109-2435 56F706-005-LI 012-9507-004 015-0341-000 015-0372-005 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT0E20-8PS CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F24-12PS CT6F9767-14-4-14S-5PC CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-20PS M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X