

This document was generated on 11/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 1731100033 | | |
|---|-------------------------|--|--|
| Status: | | | |
| | Active | | |
| Overview: | FCT D-Sub Connecto | | |
| Description: | | Waterproof D-Sub Connector, Female, Straight, PCB Throug astic Watertight Frame, Snap-in Bolt, 25 Circuits | n |
| | Hole, Gold Flating, Fla | asiic Waterlight Flame, Shap-In Bolt, 25 Circuits | A DE CONTRACTOR |
| Documents: | | | and the second second |
| Datasheet (PDF) | | RoHS Certificate of Compliance (PDF) | |
| Brochure (PDF) | | | |
| | | | |
| General | | | Series image - Reference only |
| Product Family | | D-Sub Products | |
| Series | | 173110 | EU ELV |
| IP Rating | | IP67 | Not Relevant |
| Overview | | FCT D-Sub Connectors | |
| Product Category | | D-Sub Connector | EU RoHS China RoHS |
| Product Name | | FCT Products | Compliant with |
| Туре | | Standard Density | Exemption 6(c) |
| UPC | | 889056325059 | REACH SVHC |
| | | | Contained Per - |
| Physical | | | D(2021)4569-DC (8 |
| Circuits (Loaded) | | 25 | July 2021) |
| Circuits (maximum) | | 25 | Lead |
| Color - Resin | | Red | Halogen-Free |
| Durability (mating cycles max) | | 500 Famala | <u>Status</u> |
| Gender Matarial Contact | | | Not Reviewed |
| Material - Contact Material - Resin | | Copper Alloy PBT | For more information, please visit <u>Contact US</u> |
| Material - Resin Material - Shell | | Brass | China ROHS 50 Image |
| Net Weight | | 18.200/g | ELV Not Relevant |
| Number of Rows | | 18.200/g 2 | RoHS Phthalates Not Contained |
| Orientation | | ∠ Straight | |
| PC Tail Length | | 11.20mm | |
| PCB Locator | | Yes | |
| PCB Retention | | Yes | Search Parts in this Series |
| PCB Thickness - Recommended | | 1.60mm | <u>173110</u> Series |
| Packaging Type | | Carton | |
| Panel Mount | | Rear | Mates With |
| Panel Mount Method | | Thread-In | FCT Standard Density D-Sub, Size 3, 25 |
| Pitch - Mating Interface | | 2.84mm | Position, Plug |
| Pitch - Termination I | nterface | 2.84mm | |
| Plating - Contact | | Gold over Nickel | Use With |
| Plating - Shell | | Tin | FCT D-Sub Dust Caps |
| Polarized to Mating Part | | Yes | |
| Polarized to PCB | | Yes | |
| Ports | | 1 | |
| Shielded | Orașeți | Yes | |
| Temperature Range - Operating | | -25° to +70°C | |
| Termination Style | | Through Hole | |
| Waterproof / Dustproof Waterproof / Dustproof Type | | Yes IP67 | |
| | лог туре | Γυ | |
| Electrical | | | |
| Current - Maximum | per Contact | 7.5A | |
| | | | |
| Material Info | | | |
| Engineering Number | | FWDR25S1 | |
| | | | |

This document was generated on 11/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

56F706-005-LI 56F711-015 LV242999-142T12 015-0341-000 015-0349-000 015-0350-000 015-8544-011 015-8755-001 017041-0005 020419-0104 012-0467-000 012-9507-114 020745-0008 609-25P 609-9P M24308/2-23Z M24308/2-36Z CT0-24-10SC CT0E20-8PS CT0E22-14SC CT0F16S-1SC CT0FA22-1SS CT0P14S-5SXS CT0P22-14PS CT0TA16-11SXCA232 CT0U22-14PSA206F127 CT1E20-19SS CT1E20-22SCAU-G9 CT1F22-14PC-G9 CT1FC22-2PC CT1FC24-28SSAU CT1N22-22SS CT2-10SL-3SC CT2-14S-2PCA34 CT2-18-10PS-FMLB-D CT2-18-11PCAU CT2-18-1PSAUA34 CT2-22-19SC CT2-22-19SS-A206 CT2-24-2PS CT2-28-12SC CT2-28-12SCA232 CT2-28-12SSA232 CT6-10SL-3SC CT6-10SL-4SC CT6-16-12SC CT6-18-10PSA206 CT6-18-10PSA232 CT6-18-10SSF127A206 CT6-28-22SS