

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1731110122 Status: Active Overview: FCT P-Sub Connectors Description: FCT Plastic Backshell for D-Sub Connector, Black, Shell Size 1, Straight Cable Outlet, Large Inner Chamber, with Knurled Thumb Screw Lock Series Documents: RoHS Certificate of Compliance (PDF) Sortes Image - Reference only Product Family D-Sub Products Series Series 173111 Overview FCT D-Sub Connectors Product Category Backshell EU ELV VPC B80956488235 China RoHS Physical Contra Resin Black Color - Resin Black Drassight Material - Sackshell Sortes Sol Image Mounting Syle None Sol Image Shielded None Sol Image Shielded Type Standard Sol Image State of Type Black Sol Image Pack Syle None Sol Image Shielded Type None Sol Image Shielded Type Standard Sol Type Packaging Type Standard Not Contaned					
Datasheet (PDF) Brochure (PDF) RoHS Certificate of Compliance (PDF) General Product Family D-Sub Products Series 173111 Overview FCT D-Sub Connectors Product Category Backshell Product Category Plastic UPC 88905648235 Physical Cable Diameter 4 00-11.00mm Cable Diameter 4 00-11.00mm Cable Diameter 4 00-11.00mm Cable Diameter 4 00-11.00mm Cable Diameter 4 00-11.00mm Color - Resin Black Material - Sackshell ABS / PC+ABS Material - Screw Brass Mounting Style Knurled Thumb Screw Lock Net Weight 15.000/g Orientation Straight Packaging Type Bag Plating - Backshell None Shielded No Straight Sol mage Shielded No Thread Type Standard Thread Type Standard Tightening Test Torque 40 Ncm Waterproot / Dustproof No	Status: Overview:	Active FCT D-Sub Connectors FCT Plastic Backshell for D-Sub Connector, Black, Shell Size 1, Straight Cable Outlet,			
Original Product FamilyD-Sub ProductsSeries173111OverviewFCT D-Sub ConnectorsProduct CategoryBackshellProduct NameFCT ProductsTypePlasticUPC889056488235PhysicalContained Per -Cable Diameter4.00-11.00mmCable Diameter4.00-11.00mmCable Diameter4.00-11.00mmCortained Per -BackshellABS / PC+ABSMaterial - ScrewBrassMounting StyleKnurfed Thumb Screw LockNet Weight15.000/gOrientationStraightPakaging TypeBagPlating - BackshellNoneShield TypeStandardShield Mare - Operating-35° to +120°CThread Size4-40 UNCThread Size5-120°CThread Size4-00 NcmWaterproof / DustproofNoWaterproof / DustproofNoUse With	Datasheet (PDF)	RoHS Certificate of Compliance (PDF)			
Product FamilyD-Sub ProductsSeries173111OverviewFCT D-Sub ConnectorsProduct CategoryBackshellProduct CategoryBackshellProduct NameFCT ProductsTypePlasticUPC889056488235PhysicalContained Per -Cable Diameter4.00-11.00mmColor - ResinBlackMaterial - ScrewBassMounting StyleKnurled Thumb Screw LockNet Weight0.500/ggOrientationStraightPackaging TypeBagPlating - BackshellNoneShield TypeNoneShield TypeSin dardShield Ty	General			Series image	e - Reference only
Series173111EU ELVOverviewFCT D-Sub ConnectorsNot RelevantProduct CategoryBackshellEU RoHSProduct NameFCT ProductsCompliant withTypePlasticCompliant withUPC889056488235Exemption 6(c).6(a)-IPhysicalContained Per -Cable Diameter4.00-11.00mmColor - ResinBlackMaterial - ScrewBrassMaterial - ScrewBrassMounting StyleKnurled Thumb Screw LockNet Weight15.000/gOrientationStraightPackaging TypeBagPlating - BackshellNoneShield Mape-StrongeShield Mape-StrongeShield Mape-StrongeShield Mape-StrandardThread Size4-40 UNCThread Size4-40 UNCThread Size4-40 UNCThread Size4-40 UNCThread Size4-40 UNCThread Size40 NcmWaterial InfoUse With			D-Sub Products		
OverviewFCT D-Sub ConnectorsNot RelevantProduct CategoryBackshellEU RoHSChina RoHSProduct NameFCT ProductsCompliant withTypePlasticCompliant withUPC889056488235Exemption 6(c),6(a)-1PhysicalContained Per -Coble Diameter4.00-11.00mmColor - ResinBlackMaterial - BackshellABS / PC+ABSMounting StyleKnurled Thumb Screw LockMounting StyleKnurled Thumb Screw LockNot ReviewedFor more information, please visit Contact USPackaging TypeBagPlating - BackshellNoneShield TypeNoneShield Mater-35° to +120°CThread Size4-40 UNCThread Size5-50 Mc<				EU ELV	
Product NameFCT ProductsEU RoHSChina RoHSTypePlasticCompliant withCompliant withCompliant withUPC889056488235Exemption 6(c),6(a)-1REACH SVHCContained Per -Cable Diameter4.00-11.00mmED/71/2019 (16 JulyContained Per -Color - ResinBlack2019)IeadMaterial - BackshellABS / PC+ABSIeadHalogen-FreeMouning StyleKnurled Thumb Screw LockStatusNot ReviewedNet Weight15.000/gNot ReviewedFor more information, please visit Contact USPlating - BackshellNoneChina ROHS50 ImagePlating - BackshellNoneRoHS PhthalatesNot ContainedShieldedNo-35° to +120°CNot RelevantRoHS PhthalatesThread Size4-40 UNCStandardIT31111 SeriesThread Size4-40 NcmNoIt3111 SeriesWaterproof / DustproofNoUSe WithIt3111 Series					
TypePlasticCompliant withTypePlasticExemption 6(c),6(a)-1UPC889056488235REACH SVHCPhysicalContained Per -Cable Diameter4.00-11.00mmED/71/2019 (16 JulyColor - ResinBlack2019)Material - BackshellABS / PC+ABSleadMaterial - ScrewBrassHalogen-FreeMounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImagePlating - BackshellNoneChina ROHS50 ImageShield dedNoRoHS PhthalatesNot RelevantThread Size4-40 UNCThread Size4-40 UNCThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmUse WithIts SeriesWaterproof / DustproofNoUse WithIts Series	Product Category		Backshell		
UPCResultsB89056488235Exemption 6(c),6(a)-1PhysicalContained Per -Cable Diameter4.00-11.00mmColor - ResinBlackMaterial - BackshellABS / PC+ABSMaterial - ScrewBrassMounting StyleKnurled Thumb Screw LockNet Weight15.000/gOrientationStraightPackaging TypeBagPlating - BackshellNoneShieldedNoThread Size4-40 UNCThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterpioof / DustproofNoMaterial InfoStandard	Product Name		FCT Products		<u>China RoHS</u>
Physical REACH SVHC Cable Diameter 4.00-11.00mm Contained Per - Cable Diameter 4.00-11.00mm ED/71/2019 (16 July Color - Resin Black 2019) Material - Backshell ABS / PC+ABS lead Material - Screw Brass Halogen-Free Mounting Style Knurled Thumb Screw Lock Status Not Reviewed Tormore information, please visit Contact US Packaging Type Bag Plating - Backshell None Shielded No Temperature Range - Operating -35° to +120°C Thread Size 4-40 UNC Thread Size 4-40 UNC Thread Type Standard Tightening Test Torque 40 Ncm Waterproof / Dustproof No Material Info Use With	Туре		Plastic		
PhysicalContained Per -Cable Diameter4.00-11.00mmED/71/2019 (16 JulyColor - ResinBlack2019)Material - BackshellABS / PC+ABSleadMaterial - ScrewBrassHalogen-FreeMounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImagePlating - BackshellNoneChina ROHS50 ImageShieldedNoELVNot RelevantThread Size4-40 UNCThread TypeStandardThread TypeStandard173111 SeriesWaterproof / DustproofNoUse With	UPC		889056488235		ı)-I
Cable Diameter4.00-11.00mmED/71/2019 (16 JulyColor - ResinBlack2019)Material - BackshellABS / PC+ABSleadMaterial - ScrewBrassHalogen-FreeMounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImageShield TypeNoneELVNot RelevantShield TypeNoneELVNot RelevantShieldedNoRoHS PhthalatesNot ContainedThread TypeStandardSearch Parts in this SeriesTightening Test Torque40 NcmNoWaterproof / DustproofNoUse With					
Color - ResinBlack2019)Material - BackshellABS / PC+ABSleadMaterial - ScrewBrassHalogen-FreeMounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHSPlating - BackshellNoneChina ROHSShield TypeNoneELVShield TypeNoneELVShieldaNoRoHS PhthalatesTemperature Range - Operating-35° to +120°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoMaterial InfoUse With					
Material - BackshellABS / PC+ABSleadMaterial - ScrewBrassHalogen-FreeMounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImagePlating - BackshellNoneChina ROHS50 ImageShieldedNoneELVNot RelevantShieldedNoRoHS PhthalatesNot ContainedTemperature Range - Operating-35° to +120°CRoHS PhthalatesNot ContainedThread Size4-40 UNCStandardIts Series173111 SeriesTightening Test Torque40 NcmNoUse WithUse With	•			· · ·	ý
Material - ScrewBrassHalogen-FreeMounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImagePlating - BackshellNoneELVNot RelevantShield AugeNoneELVNot RelevantShieldedNoRoHS PhthalatesNot ContainedTemperature Range - Operating-35° to +120°CRoHS PhthalatesNot ContainedThread Size4-40 UNCStandardSearch Parts in this SeriesTightening Test Torque40 NcmNo173111 SeriesWaterproof / DustproofNoUse WithUse With					
Mounting StyleKnurled Thumb Screw LockStatusNet Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImagePlating - BackshellNoneELVNot RelevantShield TypeNoneELVNot RelevantShieldedNoRoHS PhthalatesNot ContainedTemperature Range - Operating-35° to +120°CA-40 UNCThread Size4-40 UNCStandardSearch Parts in this SeriesTightening Test Torque40 NcmNoWaterproof / DustproofNoUse With					
Net Weight15.000/gNot ReviewedOrientationStraightFor more information, please visit Contact USPackaging TypeBagFor more information, please visit Contact USPlating - BackshellNoneChina ROHS50 ImageShield TypeNoneELVNot RelevantShieldedNoROHS PhthalatesNot ContainedTemperature Range - Operating-35° to +120°CROHS PhthalatesNot ContainedThread Size4-40 UNCStandardSearch Parts in this Series173111 SeriesTightening Test Torque40 NcmNo173111 SeriesUse WithMaterial InfoUse WithUse WithUse WithUse With			2.000	-	
OrientationStraightFor more information, please visit Contact USPackaging TypeBagChina ROHS50 ImagePlating - BackshellNoneChina ROHS50 ImageShield TypeNoneELVNot RelevantShieldedNoRoHS PhthalatesNot ContainedTemperature Range - Operating-35° to +120°CRoHS PhthalatesNot ContainedThread Size4-40 UNCStandardSearch Parts in this SeriesTightening Test Torque40 Ncm173111 Series173111 SeriesWaterproof / DustproofNoUse WithUse With					
Packaging TypeBagPlating - BackshellNoneShield TypeNoneShieldedNoTemperature Range - Operating-35° to +120°CThread Size4-40 UNCThread TypeStandardTightening Test Torque40 NcmWaterproof / DustproofNoUse With					
Plating - BackshellNoneChina ROHS50 ImageShield TypeNoneNot RelevantShieldedNoROHSNot RelevantTemperature Range - Operating-35° to +120°CROHS PhthalatesNot ContainedThread Size4-40 UNCStandardSearch Parts in this SeriesTightening Test Torque40 NcmNo173111 SeriesWaterproof / DustproofNoUse WithUse With				For more informatio	n, please visit <u>Contact US</u>
Shield Type None Shield Type None Shielded No Temperature Range - Operating -35° to +120°C Thread Size 4-40 UNC Thread Type Standard Tightening Test Torque 40 Ncm Waterproof / Dustproof No Material Info Use With				China POHS	50 Image
ShieldedNoRoHS PhthalatesNot ContainedShieldedNo-35° to +120°C-35° to +120°CThread Size4-40 UNC-35° to +120°CThread TypeStandardSearch Parts in this SeriesTightening Test Torque40 Ncm173111 SeriesWaterproof / DustproofNoUse With					
Temperature Range - Operating -35° to +120°C Thread Size 4-40 UNC Thread Type Standard Tightening Test Torque 40 Ncm Waterproof / Dustproof No Material Info Use With					
Thread Size 4-40 UNC Thread Type Standard Tightening Test Torque 40 Ncm Waterproof / Dustproof No Material Info Use With		Operating			
Thread Type Standard Search Parts in this Series Tightening Test Torque 40 Ncm 173111 Series Waterproof / Dustproof No Use With		Operating			
Tightening Test Torque 40 Ncm Waterproof / Dustproof No Material Info Use With	•				
Waterproof / Dustproof No Material Info Use With					
Material Info Use With				<u>173111</u> Series	
	waterproor / Dustpro	וע			
Engineering Number FKC1G-K994E FCT D-Sub, Size 1	Material Info			Use With	
	Engineering Number		FKC1G-K994E	FCT D-Sub, Size	1

This document was generated on 07/28/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Backshells category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

600X51137X600X54009X66241-12AM85049/6-38NM85049/86-12N03M85049/90-13P0370.350.0636.470.350.2435.172.350.1035.272.352.2435.173.359.4035.3829472-1PCS-E20W970-015-040R011971-009-030R121971-009-040R011971-015-040R011DPH-B-0031437013-91484402-8156-3025-EX16-500800165X02659X165X03399A165X10259X165X11359X165X11759X165X11889X165X11899X165X13019X165X13029X165X13169X165X13199X165X13239X165X13389X165X13489X165X14219X165X14429X165X14449X165X17409X165X17439X165X17569X165X17509X165X17609X165X17979XL171373971-025-030R121300X10989X165X02609X165X02639X