

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 4704400000 | | r | |
|----------------------------------|--|--|-----------------------------|-----------------------------------|
| | <u>1731130238</u> | | | |
| Status: | Active | | | |
| Overview: Description: | FCT D-Sub Connectors FCT High-Density D-Sub Cor Plating, 5.60mm Snap-in Bolt | nnector, Female, Straight, PCB Through Hole, Gold , 78 Circuits | | |
| Documents: Brochure (PDF) | | RoHS Certificate of Compliance (PDF) | | |
| General Product Family | | D-Sub Products | Series image | e - Reference only |
| Series | | <u>173113</u> | | |
| IP Rating | | IP20 | EU ELV | |
| Overview | | FCT D-Sub Connectors | Not Relevant | |
| Product Category Product Name | | D-Sub Connector | EU RoHS | China RoHS |
| | | FCT Products | Compliant with | |
| Type UPC | | High Density 191130163038 | Exemption 6(c) | |
| | | 19110010000 | REACH SVHC | |
| Physical | | | Not Reviewed | |
| Circuits (Loaded) | | 78 | Halogen-Free | |
| Circuits (maximum) | | 78 | Status | |
| Color - Resin | | Black | Not Reviewed | |
| Durability (mating cyc | les max) | 50 | | n, please visit <u>Contact US</u> |
| Gender | | Female | | ., p <u></u> |
| Material - Contact | | Copper Alloy | China ROHS | 50 Image |
| Material - Resin | | PBT | ELV | Not Relevant |
| Material - Shell | | Steel | RoHS Phthalates | Not Contained |
| Net Weight | | 19.900/g | | |
| Number of Rows | | 3 | | |
| Orientation | | Straight | Search Parts in this Series | |
| PC Tail Length | | 9.50mm | <u>173113</u> Series | |
| PCB Locator | | Yes | | |
| PCB Retention | | Yes | Mates With | |
| PCB Thickness - Rec | ommended | 1.60mm | | D-Sub, Size 5, 78 |
| Packaging Type | | Carton | Position, Plug | D-000, 0126 0, 70 |
| Panel Mount | | Rear | | |
| Panel Mount Method | | Thread-In | | |
| Pitch - Mating Interfac | | 2.08mm | | |
| Pitch - Termination In | terface | 2.08mm | | |
| Plating - Contact | | Gold over Nickel | | |
| Plating - Shell | | Tin | | |
| Polarized to Mating P | art | Yes | | |
| Polarized to PCB | | Yes | | |
| Ports | | 1 | | |
| Shielded | Operating | Yes | | |
| Temperature Range - | operating | -55° to +105°C | | |
| Termination Style | of | Through Hole | | |
| Waterproof / Dustproo | | No IP20 | | |
| Waterproof / Dustproo | л туре | IFZU | | |
| Electrical | | | | |
| Current - Maximum p | er Contact | 3.0A | | |
| Material Info | | | | |
| Engineering Number | | CT50-78S1-0981 | | |

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub High Density Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

97-3250-11 163A16809X 163A17089X 164A17199X 242A25680X L717HDB44POL2R210 L717HDEH15POL2 L777HDE15P L77HDE15SC309 163A16759X 163A16839X 163A16989X 163A17079X 164A17329X 164A18219X 241A16440X 241A16550X 241A16680X 241A20810X 241A25740X CT25-44P MDBE15PE766 L177HDE15SOL2RM23 L177HRC62S L177HRC62SVFM L177HRCG62S L717HDEG15POL2RM5 L77HDA26SVF L77HDE15SD1CO L77HDEH15SOL2RM832 DAMA-15S-WS 443895-3 106698-1 280-012K2C L177HRB44S 164A17039X 09562004701510 164A17969X L777HRC62P 241A17960X 164A18269X 280-019S1S9MEN L777HDEG15P 280-018P3S25MEGN 206504-2 40-9515HDSP 2057140-1 C115370-6002 DFMA104SNMBFR172FR022 HDC9F200E2S