

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	4704440077		
	<u>1731140277</u>		
Status:	Active		
Overview:	FCT D-Sub Connector	rs	
Description:		/ Dual-Port D-Sub Connector, Female, Right-Angle, PCB Through	La - manufacture - part
Decemption		0 Mating Cycles, Medium Mounting Height, Snap-in Bolt, 15	
	Circuits per Port	o mating oyolos, mealan moanting rieght, onap in boit, 15	
	Circuits per Port		- (
			$\bigcirc (\bigcirc (\bigcirc$
Documents:			
Datasheet (PDF)		RoHS Certificate of Compliance (PDF)	
Brochure (PDF)			(I) AAAAAAAAAAAAA (I)
			- Series image - Reference only
General			
Product Family		D-Sub Products	EUELV
Series		173114	Not Relevant
IP Rating		IP20	Not Relevant
Overview		FCT D-Sub Connectors	EU RoHS China RoHS
			Compliant
Product Category		D-Sub Connector	REACH SVHC
Product Name		FCT Products	Not Reviewed
Туре		Standard Density	
UPC		191128829786	Halogen-Free
Dhusiaal			Status
Physical		22	Not Reviewed
Circuits (Loaded)		30	For more information, please visit Contact US
Circuits (maximum)		30	
Color - Resin		Black	China ROHS Green Image
Durability (mating cycles max)		200	ELV Not Relevant
Gender		Female	RoHS Phthalates Not Contained
Material - Contact		Copper Alloy	
Material - Resin		PBT	
Material - Shell		Steel	Search Parts in this Series
Net Weight		30.000/g	<u>173114</u> Series
Number of Rows		4	<u>173114</u> Selles
Orientation		Right-Angle	
PC Tail Length		9.40mm	Mates With
PCB Locator		Yes	FCT Standard-Density D-Sub, Size 2, 15
PCB Retention		Yes	Position, Plug
PCB Thickness - Recommended		1.60mm	·
Packaging Type		Carton	
Panel Mount		Rear	
Panel Mount Method		Thread-In	
Pitch - Mating Interface		2.84mm	
Pitch - Termination Interface		2.54mm	
	lienace		
Plating - Contact		Gold over Nickel	
Plating - Shell) - ut	Tin	
Polarized to Mating F	an	Yes	
Polarized to PCB		Yes	
Ports		2	
Shielded		Yes	
Temperature Range	- Operating	-55° to +130°C	
Termination Style		Through Hole	
Waterproof / Dustpro		No	
Waterproof / Dustpro	of Type	IP20	
Fleetrical			
Electrical	0	5.04	
Current - Maximum p	er Contact	5.0A	
Material Info			
1			

FDT15SG2M

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Dualport Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 787672-3
 164A15909X
 K42X-E15S/S-A4NJ
 K42X-E9SS-A4NJ
 242A14060X
 164A15819X
 DLS2SS5AN21X
 241A22450X
 242A14180X

 241A14190X
 DLS4SS5AN21X
 178-037-513R491
 178-037-613R491
 178-009-413R571
 178-009-513R571
 178-009-613R491
 178-009

 613R691
 178-015-513R571
 178-015-613R571
 178-025-413R571
 178-025-513R571
 179-009-613R571
 179-025-513R571
 179-037-513R571

 K42X-E15S/S-A4N
 L17H2220131
 178-015-513R491
 178-025-613R481
 178-025-613R571
 178-037-513R571
 178-037-513R671

 L17H2220120
 L17H2ED0130
 L17H1740231
 L17H210120
 L17H2440120TM
 L17H1431134
 L17H1212130
 L17H221210

 L17H1222134
 L17H2662120TM
 L17H2550120
 L17H2440120
 L17H2440121
 L17H1120134
 L17H2120120
 L17H1440134

 L17H2990130

 L17H2440120
 L17H2440121
 L17H1120120
 L17H2120120
 L17H1440134