

This document was generated on 09/06/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1733590002

Status: Active

Overview: zCD Interconnect System

Description: zCD Short Body Connector Assembly, Style 1, 0.75mm Pitch, Gold (Au) OverNickel

Plated, 120 Circuits

Documents:

3D ModelApplication Specification AS-173359-0001-001 (PDF)Drawing (PDF)Application Specification AS-173359-0002-001 (PDF)3D Model (PDF)Packaging Specification PK-170834-0001-001 (PDF)

Product Specification PS-173359-0001-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL E29179

General

Product Family I/O Connectors
Series 173359
Application Wire-to-Board
Component Type Receptacle

Overview <u>zCD Interconnect System</u>

 $\begin{array}{ccc} \text{Product Name} & \text{zCD} \\ \text{Type} & \text{N/A} \end{array}$

UPC 889056590761

Physical

Circuits (Loaded)

Color - Resin

Black

Durability (mating cycles max)

Flammability

Gender

Keying to Mating Part

Lock to Mating Part

Mone

Lock to Mating Part

Material Material

Material - Metal Copper Alloy

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 33.289/g Number of Rows 4

Orientation Right Angle


PCB Locator Yes PCB Retention None PCB Thickness - Recommended 1.57mm Packaging Type Trav Panel Mount Yes Pitch - Mating Interface 0.75mm Plating min - Mating 0.762µm Plating min - Termination 0.762µm Polarized to Mating Part Yes Polarized to PCB Yes Ports

Temperature Range - Operating -40° to +85°C

Termination Interface: Style Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact 1.0A Grounding to Panel Bezel



EU ELV

Compliant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Compliant
RoHS Phthalates Not Contained

Search Parts in this Series

173359 Series

Mates With

zCD Cable Assembly 201069

Shielded No

Voltage - Maximum 30V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification AS-173359-0001-001, AS-173359-0002-001

Packaging Specification PK-170834-0001-001
Product Specification PS-173359-0001-001
Sales Drawing SD-173359-0001-000

This document was generated on 09/06/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

571763P 58098-0628 72.250.1628.2 72.250.2428.2 74720-0505 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 PCR-E36PM PCS-XE26MA+ G38A71314B 1571250010 157-22500-3 MS3471L14-19P L/C 192991-0703 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 2000314-1 200331-1 PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFD+ PCS-XE26SLFD+ G730VID08BDC24 U90B2054081210 38113800006 DP3AR020WQ1R200 Z4.102.0680.0 500-1040 500-1052 500-1054 ZP-4008-66L 0709821002 DX40-20P(55) 5554841-1 MS3474W18-8P-LC* SM3106F14S-7S-LC U90B3054061110 U65-E04-4020 ZPF0000000000097891 747360449 10099439-003C-TRLF 10137239-0021LF E9320-001-01 10137239-0011LF 70289-001LF