

This document was generated on 10/12/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	040400047		
	<u>0194280017</u>		
Status:	Active		
Overview: MX150L Industrial Sealed C		Connector System	
		ertical PCB Header, Single Row, Standard Profile, Gold (Au)	
	Plated, 2 Circuits		
Documents:			
<u>3D Model</u>		Packaging Specification PK-19428-001-001 (PDF)	
<u>3D Model (PDF)</u>		Brochure (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Product Specification PS-19427-001-001 (PDF)			Series image - Reference only
Agency Certification	on		EU ELV
UL		E152602	Not Relevant
Comorol			
General		DOB Llandere	EU RoHS China RoHS
Product Family		PCB Headers 19428	Compliant
Series Application		Power, Wire-to-Board	REACH SVHC
Comments			Not Contained Per -
		IP67 rated; conforms to UL 1977. NOT suitable for automotive applications with requirements such as	D(2021)4569-DC (8 July 2021)
		USCAR-2, USCAR-25, GMW3191, AK Testing, J2030,	Halogen-Free
		Volvo Technology Requirements, and Toyota Connector	Status
		Spec (TCS)	Low-Halogen
Overview		MX150L Industrial Sealed Connector System	For more information, please visit <u>Contact US</u>
Product Name		MX150L	To more mornation, please visit <u>contact co</u>
UPC		822348742912	China ROHS Not Relevant
			ELV Not Relevant
Physical			RoHS Phthalates Not Contained
Breakaway		No	
Circuits (Loaded)		2	
Circuits (maximum)		2	Search Parts in this Series
Durability (mating cycles max)		100	<u>19428</u> Series
Flammability		94V-0	
Glow-Wire Capable		No	Mates With
Lock to Mating Part		Yes	<u>19418</u> Receptacle Assemblies
Material - Plating Mating		Gold	13410 Receptacie Assemblies
Material - Plating Termination Net Weight		Tin 11.288/g	
Number of Rows		1.200/9	
Orientation		Vertical	
PC Tail Length		3.30mm	
PCB Locator		Yes	
PCB Retention		None	
PCB Thickness - Recommended		1.60mm	
Packaging Type		Tray	
Pitch - Mating Interface		5.84mm	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Shrouded		Fully	
Stackable		No	
Surface Mount Compatible (SMC)		No	
Temperature Range - Operating		-40° to +125°C	
Termination Interface: Style		Through Hole	
Electrical			
Current - Maximum per Contact		18.0A	
		10.0A	

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-19428-001-001 PS-19427-001-001 SD-19428-009-001

This document was generated on 10/12/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546