

This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	Part Number:	<u>0194320013</u>				
Status:		Active				
Ι.	Overview:					
	Description:	MX150L Industrial Sealed Connector System MX150L 2 Circuit Female Sealed Receptacle for 10-12 AWG Wire				
Description: WIX 150L 2 Circuit Female		MATSOL 2 CITCUIT Female Se				
	Documents:					
	3D Model		Packaging Specification PK 10422 001 001 (PDF)			
	<u>3D Model (PDF)</u>		Packaging Specification PK-19432-001-001 (PDF) Brochure (PDF)			
	Drawing (PDF)		RoHS Certificate of Compliance (PDF)			
		Product Specification PS-19432-001-001 (PDF)				
!					- Reference only	
	Agency Certification			g.	· · · · · · · · · · · · · · · · · · ·	
	CSA		LR18689	EU ELV		
	UL		E152602	Not Relevant		
	01			Not Relevant		
	General			EU RoHS	China RoHS	
	Product Family		Crimp Housings	Compliant		
	Series		<u>19432</u>	REACH SVHC		
	Application		Power, Wire-to-Wire	Not Contained Per -		
	Comments		Mat Seal Color is Yellow, Polarized to Mating Part.	D(2021)4569-DC (8		
			IP67 rated; conforms to UL 1977. NOT suitable for	July 2021)		
			automotive applications with requirements such as	Halogen-Free		
			USCAR-2, USCAR-25, GMW3191, AK Testing, J2030,	<u>Status</u>		
			Volvo Technology Requirements, and Toyota Connector	Low-Halogen		
			S	For more information	, please visit <u>Contact US</u>	
	Overview		MX150L Industrial Sealed Connector System	China DOUS	Croop Imago	
	Product Name		MX150L	China ROHS	Green Image Not Relevant	
	UPC		822350190909	RoHS Phthalates	Not Contained	
	Physical					
	Circuits (maximum)		2			
	Circuits Detail		1x1			
	Flammability		94V-0	Search Parts in this Series		
	Gender		Receptacle	<u>19432</u> Series		
	Glow-Wire Capable		No			
	Keying to Mating Part		N/A	Mates With		
Lock to Mating Part			Yes <u>194330013</u> Male Plug		lug	
Net Weight			20.000/g			
	Number of Rows		1	Use With		
	Packaging Type		Bag	19434 Female Ter	minals	
	Panel Mount		No	,		
	Pitch - Mating Interfac		5.84mm			
	Polarized to Mating P	art	Yes			
	Stackable		No			
	Temperature Range -	Operating	-40° to +125°C			
	Electrical					
	Current - Maximum pe	er Contact	30.0A			
	Material Info					
	Reference - Drawing	Reference - Drawing Numbers				
	Packaging Specificati		PK-19432-001-001			
	Product Specification		PS-19432-001-001			
	Sales Drawing		SD-19432-001-001			
1						

This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004147 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546