

## This document was generated on 01/04/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:                   | 2147501021         |  |   |
|--------------------------------|--------------------|--|---|
| Status:                        | Active             |  |   |
|                                |                    | <b>O</b> stars   |   |
|                                |                    |  |   |
|                                |                    | e-to-Micro-Fit 3.0 Female Off-the-Shelf (OTS) Cable Assembly<br>nm Length, Tin (Sn) Plating, 2 Circuits, Black |   |
|                                | Single Row, 150.00 | Tim Length, Tim (Sh) Flating, 2 Circuits, Black  |   |
| Documents:                     |                    |  |   |
| 3D Model                       |                    | Datasheet (PDF)  |   |
| Drawing (PDF)                  |                    | RoHS Certificate of Compliance (PDF)   |   |
| <u>3D Model (PDF)</u>          |                    | ······································   | •   |
|                                |                    |  | Series image - Reference only   |
| General                        |                    |  |   |
| Product Family                 |                    | Cable Assemblies   | EU ELV  |
| Series                         |                    | <u>214750</u>  | Not Relevant  |
| Application                    |                    | Power, Wire-to-Board, Wire-to-Wire   |   |
| Assembly Configuration         |                    | Dual Ended Connectors  | EU RoHS China RoHS  |
| Connector to Connector         |                    | Micro-Fit 3.0 Both Ends  | Compliant   |
| Overmolded                     |                    | No   | REACH SVHC  |
| Overview                       |                    | Micro-Fit Connector System   | Not Contained Per -   |
| Product Name                   |                    | Micro-Fit 3.0  | D(2021)4569-DC (8   |
| Туре                           |                    | Discrete Wire Assembly   | July 2021)  |
| UPC                            |                    | 193264584888   | Halogen-Free  |
|                                |                    |  | <u>Status</u>   |
| Physical                       |                    |  | Not Low-Halogen   |
| Cable Length                   |                    | 150.00mm   | For more information, please visit Contact US   |
| Circuits (Loaded)              |                    | 2  |   |
| Color - Resin                  |                    | Black  | China ROHS Green Image  |
| Gender                         |                    | Female-Female  | ELV Not Relevant  |
| Lock to Mating Part            |                    | Yes  | RoHS Phthalates Not Contained   |
| Material - Metal               |                    | Phosphor Bronze  |   |
| Material - Plating Mating      |                    | Tin  |   |
| Material - Plating Termination |                    | Tin  | Search Parts in this Series   |
| Material - Resin               |                    | Nylon  | 214750 Series   |
| Net Weight                     |                    | 4.454/g  |   |
| Number of Rows                 |                    | 1  | Mates With  |
| Packaging Type                 |                    | Bag  | Micro-Fit 3.0 Plug Housings <u>43640</u>  |
| Pitch - Mating Interface       |                    | 3.00mm   | <pre>control of the state of th</pre>        |
| Plating min - Mating           |                    | 1.016µm  | <pre><br/> <br/> <br/> <br> <br/> &lt;</br></pre> |
| Plating min - Termination      |                    | 1.016µm  |   |
| Single Ended                   |                    | No   |   |
| Termination Interface: Style   |                    | Crimp or Compression   |   |
| Wire Insulation Diameter       |                    | 1.85mm max.  |   |
| Wire Size AWG                  |                    | 18   |   |
| Wire/Cable Type                |                    | Discrete Wire, UL 10002  |   |
| Electrical                     |                    |  |   |
| Current - Maximum per Contact  |                    | 8.5A   |   |
| Voltage - Maximum              |                    | 300V AC/DC   |   |
|                                |                    |  |   |

## **Material Info**

**Reference - Drawing Numbers** Sales Drawing

2147501021-000

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150