

## This document was generated on 09/02/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Status:   | <u>2147501052</u><br>Active   |  |
|---|---|--|
| Description:  | <u>Micro-Fit Connector System</u><br>Micro-Fit 3.0 Female-to-Micro-Fit 3.0 Female Off-the-Shelf (OTS) Cable Assembl<br>Single Row, 300.00mm Length, Tin (Sn) Plating, 5 Circuits, Black | ly,  |
| Documents:<br><u>3D Model</u><br><u>3D Model (PDF)</u><br>Drawing (PDF)   | <u>Datasheet (PDF)</u><br>RoHS Certificate of Compliance (PDF)  | Series image - Reference only  |
| <b>General</b><br>Product Family<br>Series<br>Application   | Cable Assemblies<br><u>214750</u><br>Power, Wire-to-Board, Wire-to-Wire   | EU ELV<br>Not Relevant   |
| Assembly Configuration<br>Connector to Connector<br>Overmolded<br>Overview  | Dual Ended Connectors   | EU RoHSChina RoHSCompliantREACH SVHCNot Contained Per -  |
| Product Name<br>Type<br>UPC   | Micro-Fit 3.0<br>Discrete Wire Assembly<br>193264584949   | D(2021)4569-DC (8<br>July 2021)<br><u>Halogen-Free</u><br>Status   |
| Physical<br>Cable Length<br>Circuits (Loaded)   | 300.00mm<br>5   | Not Low-HalogenFor more information, please visit Contact USChina ROHSGreen Image  |
| Color - Resin<br>Gender<br>Lock to Mating Part<br>Material - Metal  | Black<br>Female-Female<br>Yes<br>Phosphor Bronze  | ELV Not Relevant<br>RoHS Phthalates Not Contained  |
| Material - Plating Mating<br>Material - Plating Termir<br>Material - Resin<br>Net Weight                          |   | Search Parts in this Series<br>214750 Series   |
| Number of Rows<br>Packaging Type<br>Pitch - Mating Interface<br>Plating min - Mating<br>Plating min - Termination | 1<br>Bag<br>3.00mm<br>1.016μm   | Mates With<br>Micro-Fit 3.0 Plug Housings <u>43640</u><br>Micro-Fit TPA Plug Housing <u>200875</u><br>Micro-Fit 3.0 Headers <u>43650</u> |
| Single Ended<br>Termination Interface: S<br>Wire Insulation Diamete<br>Wire Size AWG                              | No<br>Style Crimp or Compression  | , -  |
| Wire/Cable Type   | Discrete Wire, UL 10002   |  |
| Electrical<br>Current - Maximum per   | Contact 8.5A  |  |

Current - Maximum per Contact Voltage - Maximum

## **Material Info**

**Reference - Drawing Numbers** Sales Drawing

2147501051-000

300V AC/DC

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150