

## This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	2147502101	
	Active	
	Micro-Fit Connector System	
	Micro-Fit 3.0 Female-to-Micro-Fit 3.0 Female Off-the-Shelf (OTS) Cable Assembly,	
	Single Row, 150.00mm Length, Gold (Au) Plating, 10 Circuits, Black	
Documents:		
<u>3D Model</u>	Datasheet (PDF)	and the
Drawing (PDF)	RoHS Certificate of Compliance (PDF)	
<u>3D Model (PDF)</u>		Series image - Reference only
General		Series inlage - Relefence only
Product Family	Cable Assemblies	EU ELV
Series	<u>214750</u>	Not Relevant
Application	Power, Wire-to-Board, Wire-to-Wire	
Assembly Configuration	Dual Ended Connectors	EU RoHS China RoHS
Connector to Connector	r Micro-Fit 3.0 Both Ends	Compliant
Overmolded	No	REACH SVHC
Overview	Micro-Fit Connector System	Not Contained Per -
Product Name	Micro-Fit 3.0	D(2021)4569-DC (8
Туре	Discrete Wire Assembly	July 2021)
UPC	193264585236	Halogen-Free
		<u>Status</u>
Physical		Not Low-Halogen
Cable Length	150.00mm	For more information, please visit Contact US
Circuits (Loaded)	10	China DOUIC Crean Image
Color - Resin	Black	China ROHS Green Image
Gender	Female-Female	RoHS Phthalates Not Contained
Lock to Mating Part	Yes	RONS FILIAIALES NOL CONTAINED
Material - Metal	Phosphor Bronze	
Material - Plating Mating		
Material - Plating Termi		Search Parts in this Series
Material - Resin	Nylon	214750 Series
Net Weight	21.970/g	
Number of Rows	1	Mates With
Packaging Type	Bag	Micro-Fit 3.0 Plug Housings <u>43640</u>
Pitch - Mating Interface		<pre> <br column="1"/><br <br="" column="1"/><br column="1"/><br column="1"/><br <br="" column="&lt;/td"/></pre>
Plating min - Mating	0.762µm	<pre><br display="block"/><br <="" display="block" pre=""/><br display="block"/><br <="" br="" display="block"/><br <="" br="" display="block"/><br display="block"/><br <="" br="" display="block"/> <br <="" br="" display="block" td=""/></pre>
Plating min - Terminatio	·	
Single Ended	No Crimp or Comprossion	
Termination Interface: S	• • •	
Wire Insulation Diamete	er 1.85mm max. 18	
Wire Size AWG		
Wire/Cable Type	Discrete Wire, UL 10002	
Electrical	Contact 9.54	
Current - Maximum per	Contact 8.5A	

Current - Maximum per Contact Voltage - Maximum

## **Material Info**

**Reference - Drawing Numbers** Sales Drawing

2147502101-000

300V AC/DC

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150