

This document was generated on 09/02/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 2147561102 | | |
|--------------------------------|--|--------------------------------------|---|
| Status: | Active | | |
| Overview: | | tom | |
| Description: | <u>Micro-Fit Connector System</u> Micro-Fit 3.0 Female-to-Pigtail Off-the-Shelf (OTS) Cable Assembly, Dual Row, | | |
| • | | (Sn) Plating, 10 Circuits, Black | 7 . |
| | | | - trh |
| Documents: | | | |
| <u>3D Model</u> | | Datasheet (PDF) | Office 1 |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | |
| 3D Model (PDF) | | | |
| Conoral | | | Series image - Reference only |
| General Product Family | | Cable Assemblies | EU ELV |
| Series | | 214756 | Not Relevant |
| Application | | Power, Wire-to-Board, Wire-to-Wire | |
| Assembly Configuration | on | Dual Ended Connectors | EU RoHS China RoHS |
| Connector to Connector | | Micro-Fit 3.0-to-Pigtail | Compliant |
| Overmolded | | No | REACH SVHC |
| Overview | | Micro-Fit Connector System | Not Contained Per - |
| Product Name | | Micro-Fit 3.0 | D(2021)4569-DC (8 |
| Туре | | Discrete Wire Assembly | July 2021) |
| UPC | | 193264501359 | Halogen-Free |
| | | | <u>Status</u> |
| Physical | | | Not Low-Halogen |
| Cable Length | | 300.00mm | For more information, please visit Contact US |
| Circuits (Loaded) | | 10 | |
| Color - Resin | | Black | China ROHS Green Image |
| Gender | | Female-Pigtail | ELV Not Relevant |
| Lock to Mating Part | | Yes | RoHS Phthalates Not Contained |
| Material - Metal | | Phosphor Bronze | |
| Material - Plating Mating | | Tin | |
| Material - Plating Termination | | Tin | Search Parts in this Series |
| Material - Resin | | Nylon | 214756 Series |
| Net Weight | | 33.297/g | |
| Number of Rows | | 2 | Mates With |
| Packaging Type | | Bag | Micro-Fit 3.0 Plug Housings <u>43020</u> , Micro- |
| Pitch - Mating Interface | | 3.00mm | Fit 3.0 Headers 43045, Micro-Fit 3.0 Test |
| Plating min - Mating | | 1.016µm | Plug 44242 |
| Plating min - Termination | | 1.016µm | |
| Single Ended | | No | |
| Termination Interface | - | Crimp or Compression | |
| Wire Insulation Diame | eter | 1.85mm max. | |
| Wire Size AWG | | 18 | |
| Wire/Cable Type | | UL 1061 | |
| Electrical | - | | |
| Current - Maximum pe | er Contact | 8.5A | |
| Voltage - Maximum | | 300V AC/DC | |

Material Info

Reference - Drawing Numbers Sales Drawing

2147561100-000

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150