

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: Status: | 2147611214 Active | h Loodo | | | |
|--|----------------------|--|--|-----------------------------------|--|
| Overview: Off-the-Shelf Pre-Crimped Leads Description: Pre-Crimped Lead Micro-Fit 3.0 Fema Length, 20 AWG, Black Pre-Crimped Leads | | <u>i Leads</u> Fit 3.0 Female-to-Pigtail, Gold (Au) Plating, 300.00mm | | AMAN | |
| Documents: Drawing (PDF) Datasheet (PDF) | | RoHS Certificate of Compliance (PDF) | | A MARKE | |
| General | | | Series image | e - Reference only | |
| Product Family Series | | Cable Assemblies <u>214761</u> | EU ELV | | |
| Application | | Power, Wire-to-Board, Wire-to-Wire | Not Relevant | | |
| Assembly Configuration | | Pre-crimped Lead Only Micro-Fit 3.0 Term-to-Pigtail | EU RoHS | China RoHS | |
| Overview | | Off-the-Shelf Pre-Crimped Leads | Compliant | | |
| Product Name | | Micro-Fit 3.0 | REACH SVHC | | |
| UPC | | 193264574353 | Not Contained Per - | | |
| | | | D(2021)4569-DC (8 | | |
| Physical | | | July 2021) | | |
| Cable Length | | 300.00mm | Halogen-Free | | |
| Circuits (Loaded) | | 1 | <u>Status</u> | | |
| Color - Resin | | Black | Not Low-Halogen | | |
| Gender Material Matel | | Female-Pigtail | For more informatio | n, please visit <u>Contact US</u> | |
| Material - Metal | ing | Phosphor Bronze Gold | China ROHS | Green Image | |
| Material - Plating Material - Plating Terr | | Tin | ELV | Not Relevant | |
| Net Weight | | 6.792/g | RoHS Phthalates | Not Contained | |
| Packaging Type | | Bag | | | |
| Plating min - Mating | | 0.762µm | | | |
| Plating min - Termination | | 2.540µm | Sooroh Barta in t | his Sarias | |
| Single Ended | | Yes | 214761 Series | Search Parts in this Series | |
| Termination Interface | : Style | Crimp or Compression | <u>214701</u> Selles | | |
| Wire Insulation Diame | | 1.85mm max. | | | |
| Wire Size AWG | | 20 | Use With Micro-Fit 3.0 Receptacle Housings <u>43025</u> | | |
| Wire/Cable Type | | UL 10002 | | p-Fit BMI Panel Mount | |
| Electrical | | | | ngs 44133 , 46623 | |
| Current - Maximum pe | er Contact | 8.5A | | | |
| Material Info | | | | | |
| Reference - Drawing | Numbers | | | | |
| Sales Drawing | | 2147611211-000 | | | |

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialised Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 603PT6
 603SS6L
 604PT6
 604SS6
 706000D02F200
 910640
 1200740077
 1200740114
 AC172
 ACL-SSI-4
 R88ACAKA0015SRE

 R88ACAWL005SDE
 R88ACRGD0R3C
 1300150047
 1300660036
 1302262116
 1300150149
 1300220020
 1300220104
 1300220119

 1301240492
 1301810221
 1365323-1
 1613055
 176P12
 1971465-2
 20240400003
 20240400013
 2085828-1
 20886510030
 2-22733-8
 22733-8

 8
 CB-5PSBC-RS
 CB-704EC-RS
 CB-BATACC-RS
 CB-JST3PSW-RS
 CB-M12COM-R10
 25AC84
 25AK84X
 25AU25
 25FN82
 3011-03

 AC118
 ACL-HHS-1M(CAT5E)
 SSL009PC2DC012N
 FC2A-KC6C
 2085828-2
 20886510150
 CCS-FCB-5
 CCSFCBF2