

This document was generated on 11/08/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | <u>2153452125</u> | | | |
|--|------------------------|---|-----------------------------|-----------------------------------|
| Status: | Active | | | |
| Overview: | Off-the-Shelf Pre-Crim | abea I baau | | |
| | | uba 3.6 Female-to-Squba 3.6 Female, Tin (Sn) Plating, | | |
| | 450.00mm Length, 16 | | | ST |
| | | | 5 | |
| Documents: | | | | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | 600 | |
| Datasheet (PDF) | | | ~ | |
| | | | | |
| General | | | Series imag | ge - Reference only |
| Product Family | | Cable Assemblies | | |
| Series | | <u>215345</u> | EU ELV | |
| Assembly Configurat | tion | Pre-crimped Lead Only | Not Relevant | |
| Connector to Connector | | Squba Crimp Terminals | | |
| Overview | | Off-the-Shelf Pre-Crimped Leads | EU RoHS | <u>China RoHS</u> |
| Product Name | | Squba | Compliant | |
| UPC | | 195842349407 | REACH SVHC | |
| | | | Not Contained Per | - |
| Physical | | | D(2021)4569-DC (| 8 |
| Cable Length | | 450.00mm | July 2021) | |
| Circuits (Loaded) | | 1 | Halogen-Free | |
| Color - Resin | | Red | Status | |
| Gender | | Female-Female | Low-Halogen | |
| Lock to Mating Part | | Yes | | on, please visit <u>Contact U</u> |
| Material - Metal | | Copper Alloy | | en, ploace tien <u>contact of</u> |
| Material - Plating Ma | ıtina | Matte Tin | China ROHS | Green Image |
| Material - Resin | | Modified Polystyrene | ELV | Not Relevant |
| Net Weight | | 7.090/g | RoHS Phthalates | Not Contained |
| Number of Rows | | 1 | | |
| Packaging Type | | Bag | | |
| Pitch - Mating Interface | | 3.60mm | Or any b Danta in | |
| Plating min - Mating | | 2.540µm | Search Parts in this Series | |
| Single Ended | | No | 215345 Series | |
| Termination Interface | e. Style | Crimp or Compression | | |
| Wire Insulation Diam | 5 | 1.90mm-2.40mm | | |
| Wire Size AWG | | 16 | | |
| Wire/Cable Type | | UL 11028 | | |
| | | | | |
| Electrical | or Contact | 14.00 | | |
| Current - Maximum per Contact | | 14.0A | | |
| Voltage - Maximum | | 600V | | |
| Material Info | | | | |
| Reference - Drawin Sales Drawing | g Numbers | 2153451121-000 | | |

This document was generated on 11/08/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialised Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 603PT6
 603SS6L
 604PT6
 604SS6
 706000D02F200
 910640
 1200740077
 1200740114
 AC172
 ACL-SSI-4
 R88ACAKA0015SRE

 R88ACAWL005SDE
 R88ACRGD0R3C
 1300150047
 1300660036
 1302262116
 1300150149
 1300220020
 1300220104
 1300220119

 1301240492
 1301810221
 1365323-1
 1613055
 176P12
 1971465-2
 20240400003
 20240400013
 2085828-1
 20886510030
 2-22733-8
 22733-8

 8
 CB-5PSBC-RS
 CB-704EC-RS
 CB-BATACC-RS
 CB-JST3PSW-RS
 CB-M12COM-R10
 25AC84
 25AK84X
 25AU25
 25FN82
 3011-03

 AC118
 ACL-HHS-1M(CAT5E)
 SSL009PC2DC012N
 FC2A-KC6C
 2085828-2
 20886510150
 CCS-FCB-5
 CCSFCBF2