

## This document was generated on 11/08/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

|  | 5 <mark>3471124</mark><br>tive  |   |
|--|---|---|
| Description: Pre-                                  | <u>he-Shelf Pre-Crimped Leads</u><br>Crimped Lead Squba 3.6 Male-to-Squba 3.6 Male, Tin (Sn) Plating, 300.00m<br>oth, 16 AWG, Black | im Ji Ji  |
| Documents:<br>Drawing (PDF)<br>Datasheet (PDF)     | RoHS Certificate of Compliance (PDF)  |   |
| General  |   | Series image - Reference only                         |
| Product Family<br>Series<br>Assembly Configuration | Cable Assemblies<br><u>215347</u><br>Pre-crimped Lead Only  | EU ELV<br>Not Relevant                                |
| Connector to Connector<br>Overview                 | Squba Crimp Terminals<br>Off-the-Shelf Pre-Crimped Leads  | EU RoHS China RoHS                                    |
| Product Name<br>UPC                                | Squba<br>195842349742   | Compliant<br><u>REACH SVHC</u><br>Not Contained Per - |
| Physical<br>Cable Length                           | 300.00mm  | D(2021)4569-DC (8                                     |
| Circuits (Loaded)                                  | 1   | July 2021)<br>Halogen-Free                            |
| Color - Resin                                      | Black   | Status  |
| Gender   | Male-Male   | Low-Halogen   |
| Lock to Mating Part                                | Yes   | For more information, please visit Contact L          |
| Material - Metal                                   | Copper Alloy  |   |
| Material - Plating Mating                          | Matte Tin   | China ROHS Green Image                                |
| Material - Resin                                   | Modified Polystyrene  | ELV Not Relevant                                      |
| Net Weight   | 4.997/g   | RoHS Phthalates Not Contained                         |
| Number of Rows                                     | 1   |   |
| Packaging Type                                     | Bag   |   |
| Pitch - Mating Interface<br>Plating min - Mating   | 3.60mm<br>2.540µm   | Search Parts in this Series                           |
| Single Ended                                       | Νο  | 215347 Series   |
| Termination Interface: Style                       | Crimp or Compression  |   |
| Wire Insulation Diameter                           | 1.90mm-2.40mm   |   |
| Wire Size AWG                                      | 16  |   |
| Wire/Cable Type                                    | UL 11028  |   |
| Electrical   |   |   |
| Current - Maximum per Con<br>Voltage - Maximum     | tact 14.0A<br>600V  |   |
| Material Info                                      |   |   |
| Reference - Drawing Num                            | pers<br>2153471121-000  |   |

This document was generated on 11/08/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialised Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 603PT6
 603SS6L
 604PT6
 604SS6
 706000D02F200
 910640
 1200740077
 1200740114
 AC172
 ACL-SSI-4
 R88ACAKA0015SRE

 R88ACAWL005SDE
 R88ACRGD0R3C
 1300150047
 1300660036
 1302262116
 1300150149
 1300220020
 1300220104
 1300220119

 1301240492
 1301810221
 1365323-1
 1613055
 176P12
 1971465-2
 20240400003
 20240400013
 2085828-1
 20886510030
 2-22733-8
 22733-8

 8
 CB-5PSBC-RS
 CB-704EC-RS
 CB-BATACC-RS
 CB-JST3PSW-RS
 CB-M12COM-R10
 25AC84
 25AK84X
 25AU25
 25FN82
 3011-03

 AC118
 ACL-HHS-1M(CAT5E)
 SSL009PC2DC012N
 FC2A-KC6C
 2085828-2
 20886510150
 CCS-FCB-5
 CCSFCBF2