

## This document was generated on 01/03/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<b>2162911063</b>			
Status:	Active			
		and Contractors	3000	
Overview:		and Socket Connectors	4.4	
Description:	escription: Standard .093" Female-to-Pigtail Off-the-Shelf (OTS) Cable Assembly, Dual Row, 600.00mm Length, Tin (Sn) Plating, 6 Circuits, Natural			
	600.00mm Length,	Tin (Sn) Plating, 6 Circuits, Natural	580	
Documents:			Cart	
<u>3D Model</u>		Datasheet (PDF)		2
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		-
3D Model (PDF)			Carries ince	Deference entr
			- Series imag	e - Reference only
General				
Product Family		Cable Assemblies	EU ELV	
Series		<u>216291</u>	Not Relevant	
Application		Power, Wire-to-Board, Wire-to-Wire	EU RoHS	China RoHS
Assembly Configura		Single Ended Connector	Compliant	Clilla KOHS
Connector to Connector		Standard 093"-to-Pigtail	REACH SVHC	
Overmolded		No	Not Contained Per	
Overview		Standard .093" Pin and Socket Connectors		
Product Name		Standard .093"	D(2021)4569-DC (8 July 2021)	D
Туре		Discrete Wire Assembly	,	
UPC		193264735686	Halogen-Free	
Dhusiaal			<u>Status</u>	
Physical Cable Length		600.00mm	Not Low-Halogen	
Circuits (Loaded)		6	For more information	on, please visit <u>Contact US</u>
Color - Resin		o Natural	China ROHS	Green Image
Gender		Female-Pigtail	ELV	Not Relevant
Lock to Mating Part		Yes	RoHS Phthalates	Not Contained
Material - Metal		Brass		
Material - Plating Mating		Tin		
Material - Plating Termination		Tin		
Material - Resin		Nylon	Search Parts in this Series	
Net Weight		115.987/g	216291 Series	
Number of Rows		2		
Packaging Type		Bag	Mates With	
Pitch - Mating Interface		6.70mm	Standard .093" Plug Housing <u>19092066</u>	
Plating min - Mating		0.508µm		<u>92068</u> , <u>19092069</u> .
Plating min - Termination		0.508µm	Standard .093" P	in and Socket Header <u>5219</u>
Single Ended		Yes	,	
Termination Interface: Style		Crimp or Compression		
Wire Insulation Diameter		1.65-4.06mm		
Wire Size AWG		14		
Wire/Cable Type		UL 1015		
Electrical				
Current - Maximum per Contact		12.0A		
Voltage - Maximum		600V AC (RMS)/DC		
Material Info				

Material Info

**Reference - Drawing Numbers** Sales Drawing

2162911061-000

This document was generated on 01/03/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Specialised Cables category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 603PT6
 603SS6L
 604PT6
 604SS6
 706000D02F200
 910640
 1200740077
 1200740114
 AC172
 ACL-SSI-4
 R88ACAKA0015SRE

 R88ACAWL005SDE
 R88ACRGD0R3C
 1300150047
 1300660036
 1302262116
 1300150149
 1300220020
 1300220104
 1300220119

 1301240492
 1301810221
 1365323-1
 1613055
 176P12
 1971465-2
 20240400003
 20240400013
 2085828-1
 20886510030
 2-22733-8
 22733-8

 8
 CB-5PSBC-RS
 CB-704EC-RS
 CB-BATACC-RS
 CB-JST3PSW-RS
 CB-M12COM-R10
 25AC84
 25AK84X
 25AU25
 25FN82
 3011-03

 AC118
 ACL-HHS-1M(CAT5E)
 SSL009PC2DC012N
 FC2A-KC6C
 2085828-2
 20886510150
 CCS-FCB-5
 CCSFCBF2