

## This document was generated on 10/22/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:                   | <u>2166231043</u>   |  |                               |                                   |
|--------------------------------|---------------------|--|-------------------------------|-----------------------------------|
| Status:                        | Active              |  |                               | A AND A                           |
| Overview:                      | Squba Sealed Wire-t | o-Wire Connectors                        |                               |                                   |
| Description:                   |                     |  | //                            |                                   |
| 2000110111                     |                     | gth, Tin (Sn) Plating, 4 Circuits, Black | 41,                           |                                   |
|                                |                     |  |                               |                                   |
| Documents:                     |                     |  |                               |                                   |
| <u>3D Model</u>                |                     | Datasheet (PDF)                          |                               |                                   |
| <u>3D Model (PDF)</u>          |                     | RoHS Certificate of Compliance (PDF)     |                               | O'S A DO                          |
| Drawing (PDF)                  |                     | Kons certificate of compliance (FDF)     |                               | 60                                |
|                                |                     |  | Series image                  | e - Reference only                |
| General                        |                     |  | g.                            |                                   |
| Product Family                 |                     | Cable Assemblies                         | EU ELV                        |                                   |
| Series                         |                     | 216623                                   | Not Relevant                  |                                   |
| Application                    |                     | Power, Signal, Wire-to-Wire              |                               |                                   |
| Assembly Configurat            | tion                | Single Ended Connector                   | EU RoHS                       | <u>China RoHS</u>                 |
| Connector to Connect           |                     | Squba-to-Pigtail                         | Compliant                     |                                   |
| Overmolded                     |                     | No                                       | REACH SVHC                    |                                   |
| Overview                       |                     | Squba Sealed Wire-to-Wire Connectors     | Not Contained Per -           |                                   |
| Product Name                   |                     | Squba                                    | D(2021)4569-DC (8             |                                   |
| Туре                           |                     | Discrete Wire Assembly, Sealed Assembly  | July 2021)                    |                                   |
| UPC                            |                     | 193264746675                             | Halogen-Free                  |                                   |
|                                |                     |  | Status                        |                                   |
| Physical                       |                     |  | Not Low-Halogen               |                                   |
| Cable Length                   |                     | 600.00mm                                 |                               | n, please visit <u>Contact US</u> |
| Circuits (Loaded)              |                     | 4  |                               |                                   |
| Color - Resin                  |                     | Black                                    | China ROHS                    | Green Image                       |
| Gender                         |                     | Male-Pigtail                             | ELV                           | Not Relevant                      |
| Lock to Mating Part            |                     | Yes                                      | RoHS Phthalates               | Not Contained                     |
| Material - Metal Copper Alloy  |                     |  |                               |                                   |
| Material - Plating Ma          | iting               | Matte Tin                                |                               |                                   |
| Material - Plating Termination |                     | Matte Tin                                | Search Parts in this Series   |                                   |
| Material - Resin               |                     | Nylon                                    | 216623 Series                 |                                   |
| Net Weight                     |                     | 42.052/g                                 |                               |                                   |
| Number of Rows                 |                     | 1  | Motor W/44                    |                                   |
| Packaging Type                 |                     | Bag                                      | Mates With                    |                                   |
| Pitch - Mating Interface       |                     | 3.60mm                                   | Squba 3.6 Receptacle Assembly |                                   |
| Plating min - Mating           |                     | 2.540µm                                  | 2077820002                    |                                   |
| Plating min - Termination      |                     | 2.540µm                                  |                               |                                   |
| Single Ended                   |                     | Yes                                      |                               |                                   |
| Termination Interface: Style   |                     | Crimp or Compression                     |                               |                                   |
| Wire Insulation Diameter       |                     | 1.90mm-2.40mm                            |                               |                                   |
| Wire Size AWG                  |                     | 16                                       |                               |                                   |
| Wire/Cable Type                |                     | UL 11028                                 |                               |                                   |
| Electrical                     |                     |  |                               |                                   |
| Current - Maximum p            | per Contact         | 14.0A                                    |                               |                                   |
| Voltage - Maximum              |                     | 600V                                     |                               |                                   |
|                                |                     | 000 V                                    |                               |                                   |
| Material Info                  |                     |  |                               |                                   |

**Reference - Drawing Numbers** Sales Drawing

2166231041-000

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150