

This document was generated on 07/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>2451300430</u>				
Status: Active				2	
Overview:		<u>Nano-Fit Power Connectors</u> Nano-Fit-to-Nano-Fit Off-the-Shelf (OTS) Overmolded Cable Assembly, Dual Row,		and the second s	
Description:					
	Matte Tin (Sn) Plating, 3.0m Length, 4 Circuits, Black				
Documents:			121		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)			
Datasheet (PDF)			N IN		
General			Series imag	ge - Reference only	
Product Family		Cable Assemblies			
Series		245130	EU ELV		
Application		Power, Wire-to-Board	Not Relevant		
Assembly Configurati	on	Dual Ended Connectors	Not Kelevant		
Connector to Connect		Nano-Fit-to-Nano-Fit	EU RoHS	China RoHS	
Overmolded		Yes	Compliant		
Overview		Nano-Fit Power Connectors	REACH SVHC		
Product Name		Nano-Fit	Not Reviewed		
		Overmolded Assembly	Halogen-Free		
Type UPC		191128813839	Status		
UFC		191120013039	Not Reviewed		
Physical				on, please visit <u>Contact US</u>	
Cable Length		3.0m		on, please visit <u>contact oo</u>	
Circuits (Loaded)		4	China ROHS	Green Image	
Color - Resin		Black	ELV	Not Relevant	
Gender		Female-Female	RoHS Phthalates	Not Contained	
Lock to Mating Part		Yes			
Material - Metal		High Conductivity Copper			
Material - Plating Mating		Matte Tin			
Material - Plating Mating Material - Plating Termination		Matte Tin		Search Parts in this Series	
Material - Resin			<u>245130</u> Series	<u>245130</u> Series	
		Nylon			
Net Weight		144.800/g	Mates With	Mates With Nano-Fit Vertical Through Hole Headers <u>1053101104</u> , <u>1053121104</u> . Nano-Fit Right	
Number of Rows		2	Nano-Fit Vertical		
Packaging Type		Bag			
Pitch - Mating Interface		2.50mm		lole Headers <u>1053141104</u> .	
Plating min - Mating		2.540µm		SMT Headers 1054291104	
Plating min - Termination		2.540µm		Angle SMT Headers	
Single Ended		No		ano-Fit Plug Housing	
Termination Interface: Style		Crimp or Compression	2014441104,20		
Wire Insulation Diameter		5.30mm		···	
Wire Size AWG		20			
Wire/Cable Type		UL 2464			
Electrical					
Current - Maximum per Contact		8.0A			
Voltage - Maximum		250V AC/DC			
Material Info					
Reference - Drawing	y Numbers				
Sales Drawing		4000071377-000			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150