

This document was generated on 02/02/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0.454.000.050			
	<u>2451320650</u>			
Status:	Active			
Overview:	Micro-Fit Connector System			
Description:		Off-the-Shelf (OTS) Overmolded Cable Assembly, Dual	Same and	
	Row, 5.0m Length, 6 Circuits		000	
		·	UCU	
Documents:			Contraction and	
3D Model		Packaging Specification 245132065-PK (PDF)		
Drawing (PDF)		Datasheet (PDF)		
3D Model (PDF)		RoHS Certificate of Compliance (PDF)		
<u></u>		<u></u>	Series image	e - Reference only
General			<u>_</u>	, , , , , , , , , , , , , , , , , , ,
Product Family		Cable Assemblies	EU ELV	
Series		245132	Not Relevant	
Application		Power, Wire-to-Board, Wire-to-Wire	NOT Kelevalit	
Assembly Configurati	on	Dual Ended Connectors	EU RoHS	China RoHS
Connector to Connector		Micro-Fit 3.0 Both Ends	Compliant	
Overmolded		Yes	REACH SVHC	
Overview		Micro-Fit Connector System	Not Contained Per -	
Product Name		Micro-Fit 3.0	D(2021)4569-DC (8	
		Overmolded Assembly	July 2021)	
Type UPC		889056862189	Halogen-Free	
UFC		00900002109	Status	
Physical			Not Low-Halogen	
Cable Length		5.0m		n, please visit <u>Contact US</u>
Circuits (Loaded)		6		i, please visit <u>contact oo</u>
Color - Resin		Black	China ROHS	Green Image
Gender		Female-Female	ELV	Not Relevant
Lock to Mating Part		Yes	RoHS Phthalates	Not Contained
Material - Metal		Phosphor Bronze		
Material - Plating Mating		Tin		
Material - Plating Termination		Tin		
Material - Resin		Nylon	Search Parts in this Series	
Net Weight		362.893/g	245132 Series	
Number of Rows		2		
Packaging Type		Bag	Mates With	
Pitch - Mating Interface		3.00mm	Micro-Fit 3.0 Plug Housings 43020	
Plating min - Mating		1.016μm	<pre></pre>	Headers <u>43045</u> Micro-
Plating min - Termination		1.016µm	Fit 3.0 Test Plug 4	4242
Single Ended		No		
Termination Interface	· Style	Crimp or Compression		
Wire Insulation Diameter		5.50mm		
Wire Size AWG		20		
Wire/Cable Type		UL 2464		
Electrical				
Current - Maximum per Contact		4.0A		
Voltage - Maximum		300V AC		
Motorial Info				
Material Info Engineering Number		705161065		
		795161065		
Reference - Drawing	g Numbers			
Packaging Specification		245132065-PK		
Sales Drawing		2014400091-000		
, -				

This document was generated on 02/02/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150 DC.CAB.1900.0150