

This document was generated on 09/13/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0307005187

Status: **Active**

Overview: H-DAC 64 Unsealed Connector System

2.54mm Pitch, H-DAC 64 High Density Automotive Header, Dual Row, Right-Angle, 18 **Description:**

Circuits, Polarization Option 1, Gray, Tray

Documents:

Product Specification PS-30700-0001-001 (PDF) 3D Model **Drawing (PDF)** Packaging Specification PK-30907-260-001 (PDF)

3D Model (PDF) RoHS Certificate of Compliance (PDF)

General

PCB Headers Product Family

Series 30700

Application Automotive, Power, Wire-to-Board

Comments Polarization Option 1

H-DAC 64 Unsealed Connector System Overview

Product Name H-DAC 64 **UPC** 822348101665

Physical

Breakaway No Circuits (Loaded) 18 Circuits (maximum) 18 Color - Resin Gray Durability (mating cycles max) 10 First Mate / Last Break No Glow-Wire Capable No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Material - Metal Copper Material - Plating Mating Tin

Material - Plating Termination Nickel Material - Resin Modified Polystyrene

Net Weight 6.673/g

Number of Rows

Orientation Right Angle 3.69mm PC Tail Length Yes **PCB** Locator **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Pitch - Mating Interface 2.54mm Polarized to Mating Part Yes Polarized to PCB Yes Shrouded Fully Stackable No


Surface Mount Compatible (SMC) Temperature Range - Operating -40° to +100°C Termination Interface: Style Through Hole

No

Electrical

Current - Maximum per Contact 7.0A Voltage - Maximum 500V DC

Solder Process Data



EU ELV

Compliant

EU RoHS China RoHS

Compliant **REACH SVHC** Not Contained Per -D(2020)9139-DC (19

Jan 2021) **Halogen-Free Status**

Not Relevant

For more information, please visit Contact US

China ROHS Not Relevant Compliant ELV **RoHS Phthalates** Not Contained

Search Parts in this Series

30700 Series

Mates With

H-DAC 64 Housing 307001187

Duration at Max. Process Temperature (seconds) 040

Lead-freeProcess Capability SMC&WAVE

Max. Cycles at Max. Process Temperature 003
Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Packaging Specification PK-30907-260-001
Product Specification PS-30700-0001-001
Sales Drawing SD-30700-520-001

This document was generated on 09/13/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546