

This document was generated on 01/03/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>0347073021</u>

Status: Active

Overview:

Description: Stac64 3 Bay Vertical Headers, 50 Circuits, Bay A 10 Circuit Power Header,

Polarization A, Black; Bay B 20 Circuit Signal, Polarization C, Brown; Bay C 20 Circuits

Polarization D, Green, Tray

General

Product Family PCB Headers

Series <u>34707</u>

Application Automotive, Power, Wire-to-Board

Comments Bay A 10 Circuits Stac64 Vertical Power Header,

Polarization A. Bay B 20 Circuits Stac64 Vertical Signal

Header, Polarization C. Bay C 20 Circuits Stac64

Vertical Signal Header, Polarization D

Overview stac64 single multipocket and hybrid header system

Stac64

UPC 884982008434

Physical

Product Name

Breakaway No Circuits (Loaded) 50 Circuits (maximum) 50

Color - Resin Black, Brown, Green

Durability (mating cycles max)

First Mate / Last Break

Glow-Wire Capable

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Yes

Material - Metal Copper Alloy

Material - Plating Mating Tin Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight23.662/gNumber of Rows2OrientationVerticalPC Tail Length3.36mmPCB LocatorYesPCB RetentionNonePCB Thickness - Recommended1.57mmPackaging TypeTray

Pitch - Mating Interface 2.30mm, 2.54mm, 3.50mm, 5.25mm Pitch - Termination Interface 2.30mm, 2.54mm, 3.50mm, 5.25mm

Polarized to Mating Part

Polarized to PCB

Shrouded

Yes

Stackable

No

Surface Mount Compatible (SMC)

Nes

Temperature Range - Operating -40° to +100°C
Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact Contact Molex

Voltage - Maximum 500V

Solder Process Data

Duration at Max. Process Temperature (seconds) 040

EU ELV Compliant

EU RoHS China RoHS

Compliant REACH SVHC Contained Per -D(2021)4569-DC (8 July 2021)

Boric acid
Halogen-Free
Status

Not Relevant

For more information, please visit Contact US

China ROHS Not Relevant
ELV Compliant
RoHS Phthalates Not Contained

Search Parts in this Series

34707 Series

Mates With

31408 USCAR 2.54mm (.100") Pitch Receptacle, 31372 5.25mm (.206") Pitch Hybrid Receptacle Assembly, 34729 2.54mm (.100") Pitch Stac64 Right Angle

Receptacle

Lead-freeProcess Capability WAVE
Max. Cycles at Max. Process Temperature 003
Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Application Specification AS-34729-020-001
Packaging Specification PK-31300-892-001
Product Specification PS-31372-100-001
Sales Drawing SD-34707-300-001

This document was generated on 01/03/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004147 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546