

This document was generated on 01/10/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 0348992082 | | |
|--|------------------------------|---|---|
| Status: | Active | | |
| | | | |
| Overview: | MXP120 Sealed Connector S | | A MARINE AND A |
| Description: | | Connector with 7.00mm Clip-Slot, 2 Circuit, Dark Gray | |
| | Housing (T3-V2-S3), Backshe | ell Interface Option 2, Key C | |
| | | | 1 Alton |
| Documents: | | | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | |
| Application Specificat | tion AS-34900-0001-001 (PDF) | Product Literature (PDF) | |
| Packaging Specificati | ion PK-31301-898-001 (PDF) | | |
| | с <i>Р</i> | | Series image - Reference only |
| Application tooling | nart link | | |
| Application Tooling P | | 63824-6300 | EU ELV |
| | | 00024-0000 | |
| General | | | Compliant |
| Product Family | | Crimp Housings | EU RoHS China RoHS |
| Series | | 34899 | Compliant |
| Application | | Automotive, Body Electronics, Sealed, Wire-to-Wire | REACH SVHC |
| Comments | | See sales drawing for terminal information. | Not Contained Per - |
| Overview | | MXP120 Sealed Connector System | D(2021)4569-DC (8 |
| Polarization | | C | July 2021) |
| Product Name | | MXP120 Sealed | |
| UPC | | 889056518765 | Halogen-Free |
| | | 009000010700 | <u>Status</u> |
| Physical | | | Low-Halogen |
| Circuits (maximum) | | 2 | For more information, please visit Contact U |
| Color - Resin | | – Gray (Dark) | China ROHS Green Image |
| Gender | | Plug | ELV Compliant |
| Glow-Wire Capable | | No | RoHS Phthalates Not Contained |
| Keying to Mating Part | t | Yes | RUHS FIIIIdidies Not Contained |
| Lock to Mating Part | | Yes | |
| Material - Resin | | SPS/Nylon | |
| Net Weight | | 3.500/g | Search Parts in this Series |
| Number of Rows | | 3.500/g | 34899 Series |
| | | ı Roa | |
| Packaging Type Panel Mount | | Bag | Mates With |
| | | No 4.00mm | MXP120 Female Receptacle <u>34900</u> |
| Pitch - Mating Interface Pitch - Termination In | | 4.00mm | |
| | | | |
| Polarized to Mating P | | Yes | Use With |
| Temperature Range - | operating | -40° to +125°C | Tyco 1.2 MCON terminals Or stor Kost |
| Electrical | | | MLK 1.2 terminals |
| Current - Maximum p | er Contact | 13.0A | |
| | | | Application Tooling FAQ |
| Material Info | | | Tooling specifications and manuals are |
| | | | found by selecting the products below. |
| Reference - Drawing | | | Crimp Height Specifications are then |
| Application Specificat | | AS-34900-0001-001 | contained in the Application Tooling |
| Packaging Specificati | ion | PK-31301-898-001 | Specification document. |
| Sales Drawing | | SD-34899-2001-001, SD-34899-6001-001 | Global |
| , | | | Description Product # |
| | | | Extraction Toolkit <u>638246300</u> |
| | | | for MXP120 Sealed |
| | | | Connection System |

Connection System

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261 12110546