

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0349002101](#)
Status: **Active**
Overview: MXP120 Sealed Connector System
Description: MXP120 Sealed Receptacle, 2 Circuit, Yellow SIR Housing (T3-V2-S2 -125°C on-engine vibration), Key A, Black Insert

Documents:

| | |
|-------------------------------------------------------------------|----------------------------------------------------------------------|
| 3D Model | Application Specification AS-34900-0001-CH-001 (PDF) |
| 3D Model (PDF) | Packaging Specification PK-31301-898-001 (PDF) |
| Drawing (PDF) | Test Summary TS-34900-0002-001 (PDF) |
| Product Specification PS-34900-0001-001 (PDF) | RoHS Certificate of Compliance (PDF) |
| Application Specification AS-34900-0001-001 (PDF) | Product Literature (PDF) |

Application tooling part link

Application Tooling Part Link 63824-6300

General

| | |
|----------------|------------------------------------------------|
| Product Family | Crimp Housings |
| Series | 34900 |
| Application | Automotive, Safety, Sealed, Wire-to-Wire |
| Comments | See sales drawing for terminal information. |
| Overview | MXP120 Sealed Connector System |
| Polarization | A |
| Product Name | MXP120 Sealed |
| UPC | 889056197571 |

Physical

| | |
|-------------------------------|----------------|
| Circuits (maximum) | 2 |
| Color - Resin | Yellow |
| Gender | Receptacle |
| Glow-Wire Capable | No |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Resin | SPS/Nylon |
| Net Weight | 2.577/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 4.00mm |
| Pitch - Termination Interface | 4.00mm |
| Polarized to Mating Part | Yes |
| Temperature Range - Operating | -40° to +125°C |

Electrical

Current - Maximum per Contact 13.0A

Material Info

Reference - Drawing Numbers

| | |
|---------------------------|---------------------------------------------------------|
| Application Specification | AS-34900-0001-001, AS-34900-0001-CH-001 |
| Packaging Specification | PK-31301-898-001 |
| Product Specification | PS-34900-0001-001 |
| Sales Drawing | SD-34899-2001-001, SD-34900-2001-001, SD-34900-6001-001 |
| Test Summary | TS-34900-0002-001 |



Series image - Reference only

EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - D(2021)4569-DC (8 July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Compliant

Not Contained

Search Parts in this Series

[34900](#) Series

Mates With

MXP120 Male Blade Connector [34899](#)

Use With

MXP120 Backshell [1600912010](#) , [1600912110](#) , [1600912210](#)
MXP120 Cavity Plug [349961501](#)
MXP120 Cavity Plug Seal [349961902](#)
1.2 LL SWS from Tyco and Kostal

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Extraction Toolkit for MXP120 Sealed Connection System

[638246300](#)

This document was generated on 10/01/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Automotive Connectors](#) category:

Click to view products by [Molex](#) manufacturer:

Other Similar products are found below :

[003-018-000](#) [60403001](#) [60993906-B](#) [M902-2131](#) [M902-2161](#) [72.330.1035.1](#) [73.353.4028.0](#) [F119300-B](#) [F166900](#) [F258300-B](#) [F358300-B](#)
[F407400](#) [F444110](#) [F487000](#) [F509500B-B](#) [827153-1](#) [8N1515-32-24P](#) [9-1326729-8](#) [925474-1](#) [928905-1](#) [964562-4](#) [968782-1](#) [GT17SA-8DS-](#)
[HU](#) [98891-1012](#) [98947-1016](#) [12004475-L](#) [12010290](#) [12010309-B](#) [12015454](#) [12020219-B](#) [12020308](#) [12041318-B](#) [12052225-L](#) [12052466](#)
[12059125](#) [12064869](#) [12004327-B](#) [12010503-B](#) [12015308](#) [12015384](#) [12015909](#) [1-21030-1](#) [12041254](#) [12041318](#) [12047946-B](#) [12047957](#)
[12047957-L](#) [12059473](#) [12066261](#) [12110546](#)