

This document was generated on 08/17/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Dout Number	0040047000		
Part Number:	<u>0349617380</u>		
Status:	Active		
Overview:	Mini50 Connection Systems		the second se
Description:		Header, 3 Rows, 38 Circuit, Polarization Option A, Black,	
	Tube		and the second second second
			111111111111
Documents:			
3D Model		Packaging Specification PK-31301-688-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
	PS-34959-001-001 (PDF)	Product Literature (PDF)	
Floduct Specification	<u>F3-34939-001-001 (FDF)</u>	<u>FIOUUCI LITERATURE (FDF)</u>	Series image - Reference only
			Benes intage interence only
General		DOD Use dare	
Product Family		PCB Headers	EUELV
Series		<u>34961</u>	Not Reviewed
Application Overview		Power, Signal, Wire-to-Board <u>Mini50 Connection Systems</u>	EU RoHS China RoHS
Product Literature Ord	dor No	987650-5442	Not Reviewed
Product Name		987650-5442 Mini50	REACH SVHC
UPC		887191703787	Not Reviewed
		001131103101	Halogen-Free
Physical			Status
Breakaway		No	Not Reviewed
Circuits (Loaded)		38	Need more information on product
Circuits (maximum)		38	environmental compliance?
Color - Resin		Black	
Durability (mating cyc	les max)	10	Email productcompliance@molex.com
First Mate / Last Break		No	Please visit the Contact Us section for any
Glow-Wire Capable		No	non-product compliance questions.
Guide to Mating Part		No	China DOUC Nat Daviawad
Keying to Mating Part		Yes	China ROHS Not Reviewed ELV Not Reviewed
Lock to Mating Part		Yes	RoHS Phthalates Not Reviewed
Material - Metal		Brass	ROHS FIIII alales Not Reviewed
Material - Plating Mating		Tin over Nickel	
Material - Plating Termination		Tin over Nickel	
Material - Resin		SPS	Search Parts in this Series
Net Weight		11.230/g	<u>34961</u> Series
Number of Rows		3	
Orientation		Right Angle	Mates With
PC Tail Length		2.75mm	Mini50 Unsealed 3 Row Receptacle <u>34959</u>
PCB Locator		Yes	,
PCB Retention		None	
Packaging Type		Tube	
Pitch - Mating Interface		2.00mm	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Stackable Surface Mount Compatible (SMC)		Yes	
		No 40° to +105°C	
Temperature Range -		-40° to +105°C	
Termination Interface		Through Hole	
Electrical			
Current - Maximum pe	er Contact	4.0A	
Voltage - Maximum		500V DC	
Material Info			
Reference - Drawing Numbers			
Packaging Specification		PK-31301-688-001	

This document was generated on 08/17/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 60403001 60993906-B M902-2131 M902-2161 72.330.1035.1 73.353.4028.0 F119300-B F166900 F258300-B F358300-B F407400 F444110 F487000 F509500B-B 827153-1 8N1515-32-24P 9-1326729-8 925474-1 928905-1 964562-4 968782-1 GT17SA-8DS-HU 98891-1012 98947-1016 12004147 12004475-L 12010290 12010309-B 12015454 12020219-B 12020308 12041318-B 12052225-L 12052466 12059125 12064869 12004327-B 12010503-B 12015308 12015384 12015909 1-21030-1 12041254 12041318 12047946-B 12047957 12047957-L 12059473 12066261