

This document was generated on 03/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 0205296006 | | | |
|---|---------------------|---|-------------------------|------------------------------------|
| | 0395386006 | | 100 | |
| Status: | Active | | C. | |
| Overview: Eurostyle Terminal Blocks | | | Sol. | |
| | | prizontal Dual Level PCB Header, Closed Ends, Green | 100 | No. |
| | Housing, 6 Circuits | | Da | |
| | | | 1 Star | |
| Documents: | | | - Contraction | |
| <u>3D Model</u> | | <u>3D Model (PDF)</u> | Soft. | |
| Drawing (PDF) | | RoHS Certificate of Compliance (PDF) | 10 | a sh sh |
| | | | - | - 0 |
| General | | | Series imag | e - Reference only |
| Product Family | | Terminal Blocks | | |
| Series | | <u>39538</u> | EU ELV | |
| Application | | N/A | Not Relevant | |
| Component Type | | PCB Header | | |
| Overview | | Eurostyle Terminal Blocks | EU RoHS | <u>China RoHS</u> |
| Product Name | | ESE, Eurostyle Pluggable | Compliant | |
| Туре | | Euro Block | REACH SVHC | |
| UPC | | 822350830614 | Not Reviewed | |
| | | | Halogen-Free | |
| Physical Oir (Inc. 1971) | | 0 | <u>Status</u> | |
| Circuits (Loaded) | | 6 | Not Reviewed | |
| Entry Angle | | N/A | For more informatic | on, please visit <u>Contact US</u> |
| Lock to Mating Part | | Yes | China ROHS | Green Image |
| Number of Rows | | 2 Horizontal | ELV | Not Relevant |
| Orientation | | | RoHS Phthalates | Not Contained |
| PC Tail Length PCB Thickness - Recommended | | 3.50mm 3.00mm | | |
| POB mickness - Rec Panel Mount | commended | No | | |
| | <u></u> | 5.08mm | | |
| Pitch - Mating Interface Pitch - Termination Interface | | 5.08mm | Search Parts in | this Series |
| Polarized to Mating Part | | Yes | <u>39538</u> Series | |
| Shrouded | art | Closed Ends | | |
| Stackable | | No | Mates With | |
| Surface Mount Compatible (SMC) | | N/A | <u>39530</u> Horizontal | Plug, <u>39533</u> Vertical |
| Temperature Range - Operating | | -40° to +105°C | Plug, Most 5.08m | m (.200") Pitch Industry |
| Wire Size AWG | opolaring | N/A | Standard Plugs | |
| | | | | |
| Electrical | | | | |
| Current - Maximum p | er Contact | 15.0A | | |
| Voltage - Maximum | | 300V | | |
| Solder Process Data | 2 | | | |
| Lead-freeProcess Ca | | N/A | | |
| Leau-IreeFlocess Ca | pability | N/A | | |
| Material Info | | | | |
| Reference - Drawing | a Numbers | | | |
| Sales Drawing | | SD-39538-002-001 | | |
| | | | | |

This document was generated on 03/04/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pluggable Terminal Blocks category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 57.510.0053
 MC 1.5/ 6-ST-3.5 GY AU
 734-104
 734-302
 8-141-P
 8426620000
 860505
 860810
 GBPACX-12
 93.731.4953.0
 PV05-5,08-K

 PVP04-3,50
 PVS02-5,00
 1-1986160-3
 1377680000
 1531000000
 1546228-5
 ELFH16150
 ELFP03110
 ELFP10210
 ELFT06250

 ELVP03100
 1700410
 1700425
 1702246
 1717806
 1719600
 1734692
 1734795
 1740291
 1752441
 1752865
 1754144
 1760051
 1760336

 1777701
 1783410
 1800227
 1801080
 1836888
 1848818
 1849079
 1860870
 1876327
 1896417
 1903096
 19346
 1946309
 1970579
 1973592