

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0428786362](#)  
**Status:** **Active**  
**Overview:** Magnetic and Modular Jacks/Plugs  
**Description:** Modular Jack, Vertical, Low Profile, 6/4

**Documents:**

|  |  |
|--|--|
| <a href="#">3D Model (PDF)</a>                           | <a href="#">Packaging Specification PK-42878-492-001 (PDF)</a> |
| <a href="#">3D Model</a>                                 | <a href="#">Test Summary TS-42878-001-001 (PDF)</a>            |
| <a href="#">Drawing (PDF)</a>                            | <a href="#">RoHS Certificate of Compliance (PDF)</a>           |
| <a href="#">Product Specification PS-42878-001 (PDF)</a> |  |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E107635 |

**General**

|                           |   |
|---------------------------|---|
| Product Family            | Modular Jacks/Plugs                     |
| Series                    | <a href="#">42878</a>                   |
| Comments                  | Flush Mount Flangeless 2 PCB Thick      |
| Component Type            | PCB Jack                                |
| Magnetic                  | No                                      |
| Overview                  | <u>Magnetic and Modular Jacks/Plugs</u> |
| Performance Category      | 3                                       |
| Power over Ethernet (PoE) | N/A                                     |
| Product Name              | Modular Jack 6/4                        |
| UPC                       | 800754383196                            |

**Physical**

|                                |                      |
|--------------------------------|----------------------|
| Boot Color                     | N/A                  |
| Color - Resin                  | Black                |
| Durability (mating cycles max) | 500                  |
| Flammability                   | 94V-0                |
| Inverted / Top Latch           | N/A                  |
| Jack Height                    | 12.70mm              |
| Lightpipes/LEDs                | None                 |
| Material - Metal               | Phosphor Bronze      |
| Material - Plating Mating      | Gold                 |
| Material - Plating Termination | Tin                  |
| Material - Resin               | Polyester            |
| Net Weight                     | 1.861/g              |
| Orientation                    | Vertical (Top Entry) |
| PCB Locator                    | Yes                  |
| PCB Retention                  | Yes                  |
| PCB Thickness - Recommended    | 1.57mm               |
| Packaging Type                 | Tray                 |
| Pitch - Mating Interface       | 1.02mm               |
| Pitch - Termination Interface  | 1.27mm               |
| Plating min - Mating           | 1.270µm              |
| Plating min - Termination      | 2.540µm              |
| Port Configuration             | 1x1                  |
| Positions / Loaded Contacts    | 6/4                  |
| Surface Mount Compatible (SMC) | No                   |
| Temperature Range - Operating  | -40° to +85°C        |
| Termination Interface: Style   | Through Hole         |
| Waterproof / Dustproof         | No                   |
| Wire/Cable Type                | N/A                  |



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)4569-DC (8  
July 2021)

**Halogen-Free**

**Status**

**Not Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[42878 Series](#)

**Mates With**

FCC 68 Plugs

**Electrical**

|                               |               |
|-------------------------------|---------------|
| Current - Maximum per Contact | 1.5A          |
| Shielded                      | No            |
| Voltage - Maximum             | 150V AC (RMS) |

**Solder Process Data**

|  |      |
|--|------|
| Duration at Max. Process Temperature (seconds) | 005  |
| Lead-free Process Capability                   | WAVE |
| Max. Cycles at Max. Process Temperature        | 001  |
| Process Temperature max. C                     | 235  |

**Material Info****Reference - Drawing Numbers**

|                         |                    |
|-------------------------|--------------------|
| Packaging Specification | PK-42878-492-001   |
| Product Specification   | PS-42878-001       |
| Sales Drawing           | SDA-42878-XXXX-001 |
| Test Summary            | TS-42878-001-001   |

This document was generated on 12/21/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [MP1010RX-1000](#) [MP44RX-1000](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GAX-8-62](#) [GDCX-PA-66-50](#) [GDCX-PN-64](#) [GDCX-PN-66](#) [GDCX-PN-66-50](#) [GDLX-A-66](#) [GDLX-N-66](#) [GDLX-S-66](#) [GDLX-S-88K](#) [GDTX-S-88-50](#) [GDX-PA-1010](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#) [GMX-N-1010](#) [GMX-S-1010](#) [GMX-S-66](#) [GMX-SMT4-N-88](#) [GPX-2-64](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS2-88-3.05-50](#) [GSX-NS-88-3.05-50](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PT-J951-8C](#) [PTS-J531-8CS-50UL](#) [1-1775629-2](#) [A-2014-0-4](#) [GWLX-S-88-GR](#) [GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [RJ11FTVC2G](#) [RJ11FTVC2N](#) [RJFTVX2SA1G](#) [132764-001](#) [1413235](#) [MP88X-1000](#) [MPS88RX-5000](#) [MRJR-5481-0F2](#) [E5288-S000K3-L](#) [E5908-15A242-L](#)