

This document was generated on 09/20/2021

### PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0428788410

Status: Active

Overview: <u>Magnetic and Modular Jacks/Plugs</u>
Description: <u>Magnetic and Modular Jacks/Plugs</u>
Modular Jack, Vertical, Low Profile, 8/8

**Documents:** 

3D Model (PDF) Packaging Specification PK-42878-492-001 (PDF)

3D Model Test Summary TS-42878-001-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-42878-001 (PDF)

**Agency Certification** 

CSA LR19980 UL E107635

General

Product Family Modular Jacks/Plugs

Series <u>42878</u>

Comments Flush Mount|Flangeless|2 PCB Thick

Component Type PCB Jack Magnetic No

Overview <u>Magnetic and Modular Jacks/Plugs</u>

None

Yes

Performance Category 3
Power over Ethernet (PoE) N/A

Product Name Modular Jack 8/8, RJ45

UPC 800754383233

**Physical** 

Lightpipes/LEDs

**PCB** Locator

Boot Color N/A
Color - Resin Black
Durability (mating cycles max) 500
Flammability 94V-0
Inverted / Top Latch N/A
Jack Height 12.70mm

Material - Metal Phosphor Bronze

Material - Plating Mating
Material - Plating Termination
Tin
Material - Resin
Net Weight
Polyester
2.255/g

Orientation Vertical (Top Entry)

Yes PCB Retention PCB Thickness - Recommended 1.57mm Packaging Type Trav Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.27mm Plating min - Mating 1.270µm Plating min - Termination 2.540µm Port Configuration 1x1 Positions / Loaded Contacts 8/8

Temperature Range - Operating -40° to +85°C
Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A

Surface Mount Compatible (SMC)



Series image - Reference only

**EU ELV** 

**Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free

**Status** 

**Not Low-Halogen** 

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

42878 Series

Mates With FCC 68 Plugs

#### **Electrical**

Current - Maximum per Contact 1.5A Shielded No

Voltage - Maximum 150V AC (RMS)

#### **Solder Process Data**

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

235

### **Material Info**

### **Reference - Drawing Numbers**

Packaging Specification PK-42878-492-001
Product Specification PS-42878-001

Sales Drawing SDA-42878-XXXX-003, SDA-42878-XXXX-005

Test Summary TS-42878-001-001

This document was generated on 09/20/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L