

## This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0430201810		
	Active		
	Micro-Fit Connector System		1000
-	<b>a b</b>	ual Row, 18 Circuits, UL 94V-2, Panel Mount Ears, Glow-	and the second s
	Wire Capable, Black		
Documents:			
<u>3D Model (PDF)</u>		Test Summary 430450005-TS-000 (PDF)	
<u>3D Model</u> Drawing (PDF)		<u>Test Summary 430450006-TS-000 (PDF)</u> Test Summary TS-43045-001-001 (PDF)	
-	<u>30450001-PS-KO-000 (PDF)</u>	Test Summary TS-43045-001-001 (PDF)	Series image - Reference only
	<u>30450001-PS-SP-000 (PDF)</u>	Test Summary TS-46235-001-001 (PDF)	
Product Specification P	, , , , , , , , , , , , , , , , , , ,	RoHS Certificate of Compliance (PDF)	
	n PK-43020-001-001 (PDF)	Product Literature (PDF)	EU ELV Not Relevant
Agency Certification			EU RoHS China RoHS
CSA		LR19980	Compliant
			REACH SVHC
General			Not Contained Per -
Product Family		Crimp Housings	D(2021)4569-DC (8
Series		43020	July 2021)
Application		Power, Wire-to-Wire	Halogen-Free
Comments		This Molex product is manufactured from material	<u>Status</u>
		that has the following ratings, tested by independent	Not Low-Halogen
		agencies: a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.	For more information, please visit <u>Contact US</u>
		<pre>  deg c per lec 00095-2-13.</pre> <pre>  br&gt;b) A Glow Wire Flammability Index (GWFI) above</pre>	China ROHS Green Image
		850 deg C per IEC 60695-2-12 and hence complies with	ELV Not Relevant
		the requirements set out in the International Standard	RoHS Phthalates Not Contained
		IEC 60335-1 5th edition - household and similar	
		electrical appliances - safety, section 30 Resistance to	
		heat and fire. The customers using this product	Search Parts in this Series
		must determine its suitability for use in their particular	43020 Series
		application through testing or other acceptable means	
		as described in end-product glow-wire flammability test	Mates With
		standard IEC 60695-2-11 and any applicable product	Micro-Fit 3.0 Receptacle Housings 43025
		end-use standard(s). dr > lf it is determined during	
		the customer's evaluation of suitability, that higher performance is required, please contact Molex for	Use With
		possible product options.	Micro-Fit 3.0 Crimp Terminals <u>43031</u>
Overview		Micro-Fit Connector System	Micro-Fit 3.0 Pre-Crimped Lead <u>214762</u> ,
Product Name		Micro-Fit 3.0	214763
UPC		889056719858	
Dhusical			
Physical Circuits (maximum)		18	
Color - Resin		Black	
Flammability		94V-0	
Gender		Plug	
Glow-Wire Capable		Yes	
Keying to Mating Part		None	
Lock to Mating Part		Yes	
Material - Resin		Nylon	
Net Weight		2.200/g	
Number of Rows		2	
Packaging Type		Bag	
Panel Mount		Yes	

Pitch - Mating Interface Pitch - Termination Interface Polarized to Mating Part Stackable Temperature Range - Operating

**Material Info** 

**Reference - Drawing Numbers** Packaging Specification Product Specification

Sales Drawing Test Summary 3.00mm 3.00mm Yes No -40° to +125°C

PK-43020-001-001 430450001-PS-KO-000, 430450001-PS-SP-000, PS-43045-001 SD-43020-002-001 430450005-TS-000, 430450006-TS-000, TS-43045-001-001, TS-43045-003-001, TS-46235-001-001

## This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707 

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN 

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000