

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0430202011

Status: **Active**

Micro-Fit Connector System Overview:

Description: Micro-Fit 3.0 Plug Housing, Dual Row, 20 Circuits, UL 94V-2, Glow-Wire Capable,

Black

Documents:

Drawing (PDF) Test Summary 430450005-TS-000 (PDF) 3D Model (PDF) Test Summary 430450006-TS-000 (PDF) Test Summary TS-43045-001-001 (PDF) 3D Model Product Specification 430450001-PS-KO-000 (PDF) Test Summary TS-43045-003-001 (PDF) Product Specification 430450001-PS-SP-000 (PDF) Test Summary TS-46235-001-001 (PDF) Product Specification PS-43045-001 (PDF) RoHS Certificate of Compliance (PDF)

Packaging Specification PK-43020-001-001 (PDF) Product Literature (PDF)

Agency Certification

CSA LR19980

General

Product Family Crimp Housings

43020 Series

Application Power, Wire-to-Wire

This Molex product is manufactured from material Comments

that has the following ratings, tested by independent agencies:

 A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.

b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12 and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire.
>The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product

end-use standard(s).

If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options. Micro-Fit Connector System

Overview

Product Name Micro-Fit 3.0 **UPC** 889056719902

Physical

Circuits (maximum) 20 Color - Resin **Black** Flammability 94V-0 Gender Plug Glow-Wire Capable Yes Keying to Mating Part None Lock to Mating Part Yes Material - Resin Nylon Net Weight 2.284/g Number of Rows Packaging Type Bag Panel Mount No



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant

REACH SVHC

Not Contained Per -D(2021)4569-DC (8

July 2021)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS Green Image **ELV** Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

43020 Series

Mates With

Micro-Fit 3.0 Receptacle Housings 43025

Use With

Micro-Fit 3.0 Crimp Terminals 43031 <br Micro-Fit 3.0 Pre-Crimped Lead 214762,

214763

Pitch - Mating Interface 3.00mm
Pitch - Termination Interface 3.00mm
Polarized to Mating Part Yes
Stackable No

Temperature Range - Operating -40° to +125°C

Material Info

Reference - Drawing Numbers

Packaging Specification PK-43020-001-001

Product Specification 430450001-PS-KO-000, 430450001-PS-SP-000,

PS-43045-001

Sales Drawing SD-43020-002-001

Test Summary 430450005-TS-000, 430450006-TS-000, TS-43045-001-001, TS-43045-003-001,

TS-46235-001-001

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

892-18-020-10-001101 58102-G61-06LF 582553-1 0009485154 009176003701906 0050291907 LY20-4P-DT1-P1E-BR 02.125.8002.8

609-3404 61062-3 622-0430 622-3653LF 63453-116 636-1030 636-1427 636-3427 636-4007 641938-9 641991-4 644827-2 65817-010LF

65817-015LF 65863-015LF 66207-023LF 67095-007LF 67601157 68648-049 70.362.1628.0 70-4210 70-4226B 70-4853B 707-5020 707
5028 71.350.2428.0 71918-208LF 71961-016LF 733-134 733-162 754199-000 760-3052 787-8014-00 79531-3000 FCN-360C032-B FCN-367T-T012/H FCN-723D010/2 80.063.4001.1 800-90-001-10-001000 800-90-010-10-002000 801-43-002-10-013000 801-43-006-10-002000