

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Metal Retention Clip, Gold, Glow-Wire Capable, Black, Tape and Reel Compliant Agency Certification REACH SVHC Not Contained Per - Not Contained Per -	<u>hina RoHS</u>
Active Not Relevant Overview: Not Relevant Description: Micro-Fit 3.0 Vertical Header, 3.00mm Pitch, Dual Row, 6 Circuits, with PCB Press-fit Metal Retention Clip, Gold, Glow-Wire Capable, Black, Tape and Reel EU RoHS Compliant REACH SVHC Not Contained Per -	hina RoHS
Description: Micro-Fit 3.0 Vertical Header, 3.00mm Pitch, Dual Row, 6 Circuits, with PCB Press-fit Metal Retention Clip, Gold, Glow-Wire Capable, Black, Tape and Reel EU RoHS Compliant REACH SVHC Not Contained Per - Agency Certification Micro-Fit 3.0 Vertical Header, 3.00mm Pitch, Dual Row, 6 Circuits, with PCB Press-fit Metal Retention Clip, Gold, Glow-Wire Capable, Black, Tape and Reel EU RoHS Compliant REACH SVHC Not Contained Per -	hina RoHS
Agency Certification Not Contained Per -	
CSA LR19980 D(2021)4569-DC (8	
UL E29179 July 2021) Halogen-Free	
General Status	
Product Family PCB Headers Low-Halogen	
Declar 10045	an vinit Contact US
Series 43045 Application Power, Wire-to-Board For more information, please	se visit <u>contact 05</u>
	en Image
	Relevant
	Contained
by independent agencies:. a) A Glow Wire Ignition	
Temperature (GWIT) of at least 775 deg C per IEC	
60695-2-13 b) A Clow Wire Elamophility Index	
(GWEI) above 850 deg C per IEC 60695-2-12 and Search Parts in this Se	ries
hence complies with the requirements set out in the	
International Standard IEC 60335-1 5th edition -	
household and similar electrical appliances - safety, Mates With	
section 30 Resistance to heat and fire. <p><p> The Micro-Fit 3.0 Receptacle</p></p>	
customers using this product must determine its <pre> > Micro-Fit 3.0 TPA R</pre>	
suitability for use in their particular application through <u>172952</u> Micro-Fit 3.	.0 Cable Assembly
testing or other acceptable means as described in <u>214755</u> , <u>214756</u>	
end-product glow-wire flammability test standard	
IEC 60695-2-11 and any applicable product end-	
use standard(s). <p> If it is determined during the</p>	
customer's evaluation of suitability, that higher	
performance is required, please contact Molex for	
possible product options."""""""	
Overview microfit_30	
Product Name Micro-Fit 3.0	
UPC 800753815667	
Physical	
Breakaway No	
Circuits (Loaded) 6	
Circuits (maximum) 6	
Color - Resin Black	
Durability (mating cycles max) 30	
Flammability 94V-0	
Glow-Wire Capable Yes	
Mated Height 17.64mm	
Material - Metal Brass	
Material - Plating Mating Gold	
Material - Plating Termination Tin	
Material - Resin High Temperature Thermoplastic	
Net Weight 1.216/g	
Number of Rows 2	
Orientation Vertical	
PCB Locator Yes	
PCB Locator Yes PCB Retention Yes PCB Thickness - Recommended 1.60mm	

Packaging Type Pitch - Mating Interface Plating min - Mating Polarized to PCB Shrouded Stackable Surface Mount Compatible (SMC) Temperature Range - Operating Termination Interface: Style	Embossed Tape on Reel 3.00mm 0.381µm Yes Fully No N/A -40° to +105°C Surface Mount
Electrical Current - Maximum per Contact Voltage - Maximum	8.5A 600V
Solder Process Data Duration at Max. Process Temperature (seconds) Lead-freeProcess Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	030 REFLOW 003 260
Material Info	
Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing Symbol/Footprint Data Test Summary	430450002-PK-000 430450001-PS-KO-000, 430450001-PS-SP-000, PS-43045-001 SD-43045-006-001 SYM-43045-0615-001 430450006-TS-000, TS-43045-001-001, TS-43045-002-001, TS-46235-001-001

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000