

This document was generated on 01/05/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0432028811</u>		\sim
Status:	Active		
Overview:	Magnetic and Modular	· Jacks/Plugs	APA A
Description:		ngle, Low Profile, Shielded, All Panel Grounding Tabs, without	
Description.		p, Rear Position PCB Ground Tab, 8/10	
Documents:			
3D Model		Product Specification PS-43202-001-001 (PDF)	
Drawing (PDF)		Packaging Specification PK-43202-004-001 (PDF)	
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	- P
<u></u>		<u></u>	- Series image - Reference only
Agency Certificatio	n		
CSA		LR19980	EUELV
UL		E107635	Not Relevant
General			EU RoHS China RoHS
Product Family		Modular Jacks/Plugs	Compliant
Series		<u>43202</u>	REACH SVHC
Component Type		PCB Jack	Not Contained Per -
Magnetic		No	D(2021)4569-DC (8
Overview		Magnetic and Modular Jacks/Plugs	July 2021)
Performance Category Power over Ethernet (PoE)		3	Halogen-Free
Power over Etherner Product Name	t (POE)	N/A Modular Jack 8/10	<u>Status</u>
UPC		800756072654	Low-Halogen
		800750072054	For more information, please visit <u>Contact US</u>
Physical			China ROHS Green Image
Color - Resin		Black	ELV Not Relevant
Durability (mating cycles max)		500	RoHS Phthalates Not Contained
Flammability		94V-0	
Inverted / Top Latch		No	
Jack Height		11.81mm	Search Parts in this Series
Lightpipes/LEDs		None	43202 Series
Material - Metal		Brass, Phosphor Bronze	<u>+5202</u> Selles
Material - Plating Mating		Gold	Mates With
Material - Plating Termination		Tin	FCC 68 Plugs
Material - Resin		High Temperature Thermoplastic	FCC 08 Flugs
Net Weight Orientation		4.315/g Bight Angle (Side Entry)	
PCB Retention		Right Angle (Side Entry) Yes	
PCB Thickness - Recommended		1.57mm	
Packaging Type		Tray	
Pitch - Mating Interfa	ace	1.02mm	
Pitch - Termination I		1.27mm	
Plating min - Mating		1.270µm	
Plating min - Termination		2.540µm	
Port Configuration		1x1	
Positions / Loaded C	Contacts	8/10	
Surface Mount Com		Yes	
Temperature Range		-40° to +85°C	
Termination Interfac	e: Style	Through Hole	
Wire/Cable Type		N/A	
Electrical			
Current - Maximum	ner Contact	1.5A	
Grounding to PCB		Yes	
Grounding to Panel		Yes	
		100	

Shielded Voltage - Maximum

Solder Process Data Lead-freeProcess Capability

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing Yes 150V AC (RMS)

WAVE

PK-43202-004-001 PS-43202-001-001 SDA-43202-001

This document was generated on 01/05/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS2-88-3.05 O GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 E5288-S000K3-L E5908-15A242-L 155302-001 AX100653