

This document was generated on 01/05/2022

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0432498104

Status: **Active** 

Overview: Magnetic and Modular Jacks/Plugs

Modular Jack, Right-Angle, Low Profile, 8/8, Panel Stops **Description:** 

**Documents:** 

Drawing (PDF) Product Specification PSX-43249-001 (PDF) 3D Model (PDF) Packaging Specification PK-43249-004-001 (PDF)

RoHS Certificate of Compliance (PDF) 3D Model

**Agency Certification** 

CSA LR19980 UL E107635

General

**Product Family** Modular Jacks/Plugs

43249 Series Component Type PCB Jack Magnetic No

Overview Magnetic and Modular Jacks/Plugs

Performance Category Power over Ethernet (PoE) N/A

**Product Name** Modular Jack 8/8, RJ45

**UPC** 800754315128

**Physical** 

**Boot Color** N/A Color - Resin Black Durability (mating cycles max) 500 Flammability 94V-0 Inverted / Top Latch Nο Jack Height 12.83mm Lightpipes/LEDs

Material - Metal **Phosphor Bronze** 

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

None

Net Weight

Orientation Right Angle (Side Entry)

**PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.27mm Plating min - Mating 1.270µm Plating min - Termination 2.540µm Port Configuration 1x1 Positions / Loaded Contacts 8/8 Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -40° to +85°C Termination Interface: Style Through Hole

Waterproof / Dustproof Nο Wire/Cable Type N/A

**Electrical** 

Current - Maximum per Contact 1.5A



**EU ELV** 

**Not Relevant** 

**EU RoHS China RoHS** 

Compliant **REACH SVHC** Not Contained Per -D(2021)4569-DC (8 July 2021)

**Halogen-Free** 

**Status** 

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image Not Relevant ELV RoHS Phthalates Not Contained

Search Parts in this Series

**43249 Series** 

**Mates With** FCC 68 Plugs Shielded

Voltage - Maximum 150V AC (RMS)

**Solder Process Data** 

Lead-freeProcess Capability WAVE

**Material Info** 

**Reference - Drawing Numbers** 

Packaging Specification PK-43249-004-001
Product Specification PSX-43249-001
Sales Drawing SDA-43249-001

This document was generated on 01/05/2022

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L