

This document was generated on 01/05/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0	432498909			^
	ctive			$\langle \$
~ ~				
	<u> </u>		8	
Description: M	odular Jack, Right-Angle,	Low Profile, 8/10, Panel Stops		
Documents:				M
3D Model		Product Specification PSX-43249-001 (PDF)		
Drawing (PDF)		Packaging Specification PK-44050-004-001 (PDF)		
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	- Ca	and a
			- Series imag	e - Reference only
Agency Certification CSA		LR19980	Conce inage	
UL		E107635	EU ELV	
0L		E107033	Not Relevant	
General			Not Relevant	
Product Family		Modular Jacks/Plugs	EU RoHS	China RoHS
Series		43249	Compliant	
Component Type		PCB Jack	REACH SVHC	
Magnetic		No	Not Contained Per -	
Overview		Magnetic and Modular Jacks/Plugs	D(2021)4569-DC (8	
Performance Category		3	July 2021)	
Power over Ethernet (PoE	-)	N/A	Halogen-Free	
Product Name	-)	Modular Jack 8/10	Status	
UPC		800756394596	Low-Halogen	
		000700004000	_	n, please visit <u>Contact U</u>
Physical				
Boot Color		N/A	China ROHS	Green Image
Color - Resin		Black	ELV	Not Relevant
Durability (mating cycles r	nax)	500	RoHS Phthalates	Not Contained
Flammability		94V-0		
Inverted / Top Latch		No		
Jack Height		13.00mm	Connah Danta in t	his Carias
Lightpipes/LEDs		None	Search Parts in t	nis Series
Material - Metal		Phosphor Bronze	43249 Series	
Material - Plating Mating		Gold		
Material - Plating Termina	tion	Tin	Mates With	
Material - Resin		High Temperature Thermoplastic	FCC 68 Plugs	
Net Weight		5.332/g	,	
Orientation		Right Angle (Side Entry)		
PCB Locator		Yes		
PCB Retention		Yes		
PCB Thickness - Recomn	nended	1.57mm		
Packaging Type		Tray		
Pitch - Mating Interface		1.02mm		
Pitch - Termination Interfa	ice	1.27mm		
Plating min - Mating		1.270µm		
Plating min - Termination		2.540µm		
Port Configuration		1x1		
Positions / Loaded Contac	rte	8/10		
Surface Mount Compatible		Yes		
		-40° to +85°C		
Temperature Range - Ope				
Termination Interface: Sty		Through Hole		
Waterproof / Dustproof		No		
Wire/Cable Type		N/A		
Electrical				

Current - Maximum per Contact

1.5A

Grounding to PCB Grounding to Panel Shielded Voltage - Maximum

Solder Process Data Lead-freeProcess Capability

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing Yes Top Panel Ground Tabs Yes 150V AC (RMS)

WAVE

PK-44050-004-001 PSX-43249-001 SDA-43249-001

This document was generated on 01/05/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L