

This document was generated on 09/23/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0432498927

Status: Active

Overview: Magnetic and Modular Jacks/Plugs

Description: Modular Jack, Right-Angle, Low Profile, 8/8, Panel Stops

Documents:

<u>3D Model</u> <u>Packaging Specification PK-44050-004-001 (PDF)</u>

Drawing (PDF) RoHS Certificate of Compliance (PDF)

3D Model (PDF)

Agency Certification

CSA LR19980 UL E107635

General

Product Family Modular Jacks/Plugs

Series 43249
Component Type PCB Jack
Magnetic No

Overview <u>Magnetic and Modular Jacks/Plugs</u>

Performance Category 3
Power over Ethernet (PoE) N/A

Product Name Modular Jack 8/8, RJ45

UPC 800756395517

Physical

Lightpipes/LEDs

Boot Color N/A
Color - Resin Black
Durability (mating cycles max) 500
Flammability 94V-0
Inverted / Top Latch No
Jack Height 13.00mm

Material - Metal Brass, Phosphor Bronze

Material - Plating Mating Gold
Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

None

Net Weight 5.183/g

Orientation Right Angle (Side Entry)


PCB Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Tray Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.27mm Plating min - Mating 1.270µm Plating min - Termination 2.540µm Port Configuration 1x1 Positions / Loaded Contacts 8/8 Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -40° to +85°C
Termination Interface: Style Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A

Electrical

Current - Maximum per Contact 1.5A



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free Status

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

43249 Series

Mates With FCC 68 Plugs

Grounding to PCB Yes
Grounding to Panel Yes
Shielded Yes

Voltage - Maximum 150V AC (RMS)

Solder Process Data

Lead-freeProcess Capability WAVE

Material Info

Reference - Drawing Numbers

Packaging Specification PK-44050-004-001 Sales Drawing SDA-43249-001

This document was generated on 09/23/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L