

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0433752001](#)  
**Status:** **Active**  
**Overview:** Sabre Power Connector  
**Description:** Sabre Single Crimp Terminal, Female, 18-20 AWG, 2.84mm Max. Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact with TPA

**Documents:**

<a href="#">Drawing (PDF)</a>	<a href="#">Test Summary 444410000-TS-000 (PDF)</a>
<a href="#">Product Specification PS-44441-9999-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>
<a href="#">Packaging Specification 433750000-PK-000 (PDF)</a>	<a href="#">Product Literature (PDF)</a>

**General**

Product Family	Crimp Terminals
Series	<a href="#">43375</a>
Application	Power, Wire-to-Wire
Comments	For single crimping of 18-20 AWG wire in a side-by-side orientation. Terminal mates to 3.18mm wide x 0.51mm thick flat blade PC tab.
Crimp Quality Equipment Overview	Yes
Product Name	<a href="#">Sabre Power Connector</a>
UPC	Sabre 883906722296

**Physical**

Durability (mating cycles max)	25
Gender	Female
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.320/g
Packaging Type	Reel
Plating min - Mating	0.508µm
Plating min - Termination	0.508µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	2.84mm max.
Wire Size AWG	18, 20
Wire Size mm <sup>2</sup>	N/A

**Electrical**

Current - Maximum per Contact	18.0A
Voltage - Maximum	600V

**Material Info**

**Reference - Drawing Numbers**

Packaging Specification	433750000-PK-000
Product Specification	PS-44441-9999-001
Sales Drawing	SD-43375-301-001
Test Summary	444410000-TS-000



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)4569-DC (8  
July 2021)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[43375 Series](#)

**Use With**

[44441 Receptacle Housings](#)

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

Description	Product #
-------------	-----------

Extraction and Activation Tool	<a href="#">638132700</a>
Hand Crimp Tool for Female Flat Blade Crimp Terminals	<a href="#">638232500</a>
Hand Crimp Tool for Female Flat Blade Crimp Terminals	<a href="#">638232600</a>
FineAdjust Applicator for Flat Blade Crimp	<a href="#">639012500</a>

Terminal, 18-20  
AWG, UL 1007 Wire  
FineAdjust Applicator 639012600  
for Flat Blade Crimp  
Terminal, 18-20  
AWG, UL 1015 Wire  
T2 Terminator for 639112500  
Flat Blade Crimp  
Terminals, 18-20  
AWG, UL1007 Wire  
T2 Terminator for 639112600  
Flat Blade Crimp  
Terminals, 18-20  
AWG, UL1015 Wire

This document was generated on 09/27/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)  
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)