

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** **0436500614**  
**Status:** **Active**  
**Overview:** Micro-Fit Connector System  
**Description:** Micro-Fit 3.0 Right-Angle Header, 3.00mm Pitch, Single Row, 6 Circuits, with Solder Tab, Gold, Glow-Wire Capable, Black, Tape and Reel

**Documents:**

|                                                                 |                                                                |
|-----------------------------------------------------------------|----------------------------------------------------------------|
| <a href="#">Drawing (PDF)</a>                                   | <a href="#">Packaging Specification 708730000-PK-000 (PDF)</a> |
| <a href="#">3D Model (PDF)</a>                                  | <a href="#">Test Summary 430450006-TS-000 (PDF)</a>            |
| <a href="#">3D Model</a>                                        | <a href="#">Test Summary TS-43045-001-001 (PDF)</a>            |
| <a href="#">Product Specification 436500001-PS-JA-000 (PDF)</a> | <a href="#">Test Summary TS-43045-002-001 (PDF)</a>            |
| <a href="#">Product Specification 436500001-PS-KO-000 (PDF)</a> | <a href="#">Test Summary TS-46235-001-001 (PDF)</a>            |
| <a href="#">Product Specification 436500001-PS-SP-000 (PDF)</a> | <a href="#">Datasheet (PDF)</a>                                |
| <a href="#">Product Specification PS-43650-001 (PDF)</a>        | <a href="#">Symbol Footprint Data SYM-43650-0612-001 (PDF)</a> |
| <a href="#">Packaging Specification 436500001-PK-000 (PDF)</a>  | <a href="#">RoHS Certificate of Compliance (PDF)</a>           |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |


**General**

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Family | PCB Headers                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Series         | 43650                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Application    | Power, Wire-to-Board                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Comments       | <p>High Temperature Square Pin Solder Type&lt;P&gt;&lt;P&gt;This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. &lt;P&gt;&lt;P&gt; The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). &lt;P&gt; If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options. """"""</p> |

|              |                                   |
|--------------|-----------------------------------|
| Overview     | <u>Micro-Fit Connector System</u> |
| Product Name | Micro-Fit 3.0                     |
| UPC          | 800753791794                      |

**Physical**

|                                |        |
|--------------------------------|--------|
| Breakaway                      | No     |
| Circuits (Loaded)              | 6      |
| Circuits (maximum)             | 6      |
| Color - Resin                  | Black  |
| Durability (mating cycles max) | 30     |
| Flammability                   | 94V-0  |
| Glow-Wire Capable              | Yes    |
| Mated Height                   | 6.98mm |



**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)4569-DC (8  
July 2021)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[43650 Series](#)

**Mates With**

Micro-Fit 3.0 Receptacle Housing [43645](#)  
 <br>Micro-Fit 3.0 TPA Receptacle Housing  
[171850](#) <br> Micro-Fit 3.0 Cable Assembly  
[2147502061](#) , [2147502062](#) , [2147502063](#) ,  
[2147512061](#) , [2147512062](#) , [2147512063](#)

|                                                |                                                                                |
|------------------------------------------------|--------------------------------------------------------------------------------|
| Material - Metal                               | Brass                                                                          |
| Material - Plating Mating                      | Gold                                                                           |
| Material - Plating Termination                 | Tin                                                                            |
| Material - Resin                               | High Temperature Thermoplastic                                                 |
| Net Weight                                     | 1.098/g                                                                        |
| Number of Rows                                 | 1                                                                              |
| Orientation                                    | Right Angle                                                                    |
| PCB Locator                                    | Yes                                                                            |
| PCB Retention                                  | Yes                                                                            |
| PCB Thickness - Recommended                    | 1.60mm                                                                         |
| Packaging Type                                 | Embossed Tape on Reel                                                          |
| Pitch - Mating Interface                       | 3.00mm                                                                         |
| Plating min - Mating                           | 0.762µm                                                                        |
| Plating min - Termination                      | 2.540µm                                                                        |
| Polarized to PCB                               | Yes                                                                            |
| Shrouded                                       | Fully                                                                          |
| Stackable                                      | No                                                                             |
| Temperature Range - Operating                  | -40° to +105°C                                                                 |
| Termination Interface: Style                   | Surface Mount                                                                  |
| <b>Electrical</b>                              |                                                                                |
| Current - Maximum per Contact                  | 8.5A                                                                           |
| Voltage - Maximum                              | 600V                                                                           |
| <b>Solder Process Data</b>                     |                                                                                |
| Duration at Max. Process Temperature (seconds) | 030                                                                            |
| Lead-free Process Capability                   | REFLOW                                                                         |
| Max. Cycles at Max. Process Temperature        | 003                                                                            |
| Process Temperature max. C                     | 260                                                                            |
| <b>Material Info</b>                           |                                                                                |
| <b>Reference - Drawing Numbers</b>             |                                                                                |
| Packaging Specification                        | 436500001-PK-000, 708730000-PK-000                                             |
| Product Specification                          | 436500001-PS-JA-000, 436500001-PS-KO-000,<br>436500001-PS-SP-000, PS-43650-001 |
| Sales Drawing                                  | SD-43650-005-001                                                               |
| Symbol/Footprint Data                          | SYM-43650-0612-001                                                             |
| Test Summary                                   | 430450006-TS-000, TS-43045-001-001,<br>TS-43045-002-001, TS-46235-001-001      |

This document was generated on 09/13/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)  
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)  
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)  
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)