

Process Temperature max. C

This document was generated on 09/02/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 044	41440013			\sim
Status: Active				
Overview: Magnetic and Modular Jacks/Plugs			<	
Description: Mod	lular Jack, Right-Angle, I	Low Profile, Surface Mount, 8/8		
Documents:			1	
<u>3D Model</u>		Product Specification PS-43743-0001-001 (PDF)	Las	18
<u>Drawing (PDF)</u>		Packaging Specification PK-70873-700-001 (PDF)		
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)		LO
Agency Certification			– Series image	e - Reference only
CSA		LR19980		·
UL		E107635	EU ELV	
0L		2107000	Not Relevant	
General				
Product Family		Modular Jacks/Plugs	EU RoHS	China RoHS
Series		<u>44144</u>	Compliant	
Component Type		PCB Jack	REACH SVHC	
Magnetic		No	Not Contained Per -	
Overview		Magnetic and Modular Jacks/Plugs	D(2021)4569-DC (8	
Performance Category		3	July 2021)	
Power over Ethernet (PoE)		N/A	Halogen-Free	
Product Name		Modular Jack 8/8, RJ45	Status	
UPC		800753923096	Low-Halogen	
		000700020000		n, please visit <u>Contact L</u>
Physical				
Color - Resin		Black	China ROHS	Green Image
Durability (mating cycles ma	ax)	500	ELV	Not Relevant
Flammability		94V-0	RoHS Phthalates	Not Contained
Inverted / Top Latch		No		
Jack Height		11.73mm		
Lightpipes/LEDs		None	Counch Doute in t	hia Cariaa
Material - Metal		Phosphor Bronze	Search Parts in t	nis Series
Material - Plating Mating		Gold	44144 Series	
Material - Plating Termination	on	Tin		
Material - Resin		High Temperature Thermoplastic	Mates With	
Net Weight		2.682/g	FCC 68 Plugs	
Orientation		Right Angle (Side Entry)		
PCB Retention		Yes		
Packaging Type		Embossed Tape on Reel		
Pitch - Mating Interface		1.02mm		
Pitch - Termination Interface	<u>م</u>	1.27mm		
Plating min - Mating		0.380µm		
Plating min - Termination		2.540µm		
Port Configuration				
Positions / Loaded Contacts	、	1x1 9/9		
		8/8 40° to 170°C		
Temperature Range - Opera		-40° to +70°C		
Termination Interface: Style Wire/Cable Type		Surface Mount N/A		
Electrical		4.54		
Current - Maximum per Con	ntact	1.5A		
Shielded		No		
Voltage - Maximum		150V AC (RMS)		
Solder Process Data				
Lead-freeProcess Capability		REFLOW		
Process Temperature max	C	235		

235

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-70873-700+-001 PS-43743-0001-001 SD-44144-001-001

This document was generated on 09/02/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS2-88-3.05 O GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L 155302-001