

This document was generated on 09/23/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	umber: 0441440014			\sim
Status: Active			/	
	iew: Magnetic and Modular Jacks/Plugs			
Overview:			\leq	
Description:	Modular Jack, Right-	Angle, Low Profile, Surface Mount, 6/4		2.
Documents:			16/2	
<u>3D Model</u>		Product Specification PS-43743-0001-001 (PDF)	LAS	118
<u>3D Model (PDF)</u>		Packaging Specification PK-70873-700-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		1 C
Agency Certification	n		Series imag	e - Reference only
CSA		LR19980		
UL		E107635	EU ELV	
			Not Relevant	
General Droduct Fomily		Medular Jacks/Dlugs		Chine DallO
Product Family		Modular Jacks/Plugs	EU RoHS	<u>China RoHS</u>
Series		<u>44144</u>	Compliant	
Component Type		PCB Jack	REACH SVHC	
Magnetic		No	Not Contained Per	
Overview		Magnetic and Modular Jacks/Plugs	D(2021)4569-DC (8	3
Performance Catego		3	July 2021)	
Power over Ethernet	(PoE)	N/A	Halogen-Free	
Product Name		Modular Jack 6/4	Status	
UPC		800753923102	Low-Halogen	
			_	on, please visit <u>Contact U</u>
Physical				
Color - Resin		Black	China ROHS	Green Image
Durability (mating cyc	cles max)	500	ELV	Not Relevant
Flammability		94V-0	RoHS Phthalates	Not Contained
Inverted / Top Latch		No	,	
Jack Height		11.73mm		
Lightpipes/LEDs		None		
Material - Metal		Phosphor Bronze	Search Parts in this Series	
Material - Plating Mating		Gold	44144 Series	
Material - Plating Ter		Tin		
Material - Resin		High Temperature Thermoplastic	Mates With	
Net Weight		2.191/g	FCC 68 Plugs	
Orientation		Right Angle (Side Entry)		
PCB Retention		Yes		
Packaging Type		Embossed Tape on Reel		
Pitch - Mating Interfa		1.02mm		
Pitch - Termination Ir	nterface	1.27mm		
Plating min - Mating		0.380µm		
Plating min - Termina	ation	2.540µm		
Port Configuration		1x1		
Positions / Loaded C	ontacts	6/4		
Temperature Range	- Operating	-40° to +70°C		
Termination Interface		Surface Mount		
Wire/Cable Type	-	N/A		
Electrical				
Current - Maximum p	per Contact	1.5A		
Shielded		I.SA No		
Voltage - Maximum		150V AC (RMS)		
Solder Process Dat				
Lead-freeProcess Ca	apability	REFLOW		

Lead-freeProcess Capability Process Temperature max. C REFLOW 235

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-70873-700+-001 PS-43743-0001-001 SD-44144-001-001, SD-44144-001-002

This document was generated on 09/23/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L