

This document was generated on 09/14/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0441500006

Status: Active

Overview: Magnetic and Modular Jacks/Plugs

**Description:** Modular Jack, Right-Angle, Low Profile, 8/8, 4 Ports

**Documents:** 

3D Model Packaging Specification PK-44150-004-000 (PDF)

Drawing (PDF)

3D Model (PDF)

Test Summary TS-44050-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR19980 UL E107635

General

Product Family Modular Jacks/Plugs

Series <u>44150</u>

Comments External Shield Component Type PCB Jack No

Overview <u>Magnetic and Modular Jacks/Plugs</u>

Performance Category 5, 5e Power over Ethernet (PoE) N/A

Product Name Modular Jack 8/8, RJ45

UPC 800754812733

**Physical** 

Color - ResinBlackDurability (mating cycles max)500Flammability94V-0Inverted / Top LatchNoJack Height13.31mmLightpipes/LEDsNone

Material - Metal Phosphor Bronze

Material - Plating Mating Gold
Material - Plating Termination Tin
Material - Resin Nylon
Net Weight 10.512/q

Orientation Right Angle (Side Entry)

**PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Trav Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.27mm Plating min - Mating 1.270µm Plating min - Termination 2.540µm **Port Configuration** 1x4 Positions / Loaded Contacts 8/8

Temperature Range - Operating -40° to +85°C
Termination Interface: Style Through Hole


Wire/Cable Type N/A

**Electrical** 

Current - Maximum per Contact 1.5A Shielded Yes

Voltage - Maximum 150V AC (RMS)

**Solder Process Data** 



**EU ELV Not Relevant** 

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -D(2021)4569-DC (8 July 2021)

Halogen-Free

**Status** 

**Not Low-Halogen** 

For more information, please visit Contact US

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

44150 Series

Mates With FCC 68 Plugs

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

260

## **Material Info**

**Reference - Drawing Numbers** 

Packaging Specification PK-44150-004-000
Sales Drawing SD-44150-002-001
Test Summary TS-44050-001-001

This document was generated on 09/14/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L 155302-001