

Voltage - Maximum

## This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0445200001			
	Active			
,		nalvo/Divero	1	. 1. 1-
<u></u>			N	LLLE
Description:	lodular Jack, Right-Angl	le, Shielded, Stacked, 8/8, 8 Ports	J-F-	LLLL
Documents:				
Drawing (PDF)		Packaging Specification PK-44520-003-001 (PDF)		
<u>3D Model (PDF)</u>		Test Summary TS-44170-001-001 (PDF)		
<u>3D Model</u>		RoHS Certificate of Compliance (PDF)		
Agency Certification			– Series image	e - Reference only
CSA		LR19980		
UL		E107635	EU ELV	
0E		E107033	Not Relevant	
General			Not Relevant	
Product Family		Modular Jacks/Plugs	EU RoHS	China RoHS
Series		44520	Compliant	<u></u>
Comments		High Speed Multi-Port	REACH SVHC	
Component Type		PCB Jack	Not Contained Per -	
Magnetic		No	D(2020)9139-DC (1	
Overview		Magnetic and Modular Jacks/Plugs	Jan 2021)	•
Performance Category		5, 5e	Halogen-Free	
Power over Ethernet (Po		N/A	Status	
Product Name	,_)	Modular Jack 8/8, RJ45	Not Low-Halogen	
UPC		800753265165		n, please visit Contact
Physical				
Physical Color - Resin		Black	China ROHS	Green Image
			ELV	Not Relevant
Durability (mating cycles	max)	500	RoHS Phthalates	Not Contained
Flammability		94V-0		
Inverted / Top Latch		Yes		
Jack Height		25.41mm	Search Parts in t	his Series
Lightpipes/LEDs		None	44520 Series	
Material - Metal		Brass, Phosphor Bronze	<u>44320</u> Series	
Material - Plating Mating		Gold		
Material - Plating Termination		Tin	Mates With	
Material - Resin		Polyester	FCC 68 Plugs	
Net Weight		35.586/g		
Orientation		Right Angle (Side Entry)		
PCB Retention		Yes		
PCB Thickness - Recom	mended	1.60mm		
Packaging Type		Tray		
Pitch - Mating Interface		1.02mm		
Pitch - Termination Inter	face	1.27mm		
Plating min - Mating		1.270µm		
Plating min - Termination	า	2.540µm		
Port Configuration		2x4		
Positions / Loaded Conta	acts	8/8		
Surface Mount Compatib	ole (SMC)	No		
Temperature Range - Op		-40° to +80°C		
Termination Interface: St		Through Hole		
Wire/Cable Type	-	N/A		
Electrical				
Current - Maximum per (	Contact	1.5A		
Shielded		Yes		
Voltage - Maximum		125\/		

125V

Solder Process Data Lead-freeProcess Capability

WAVE

#### **Material Info**

#### **Reference - Drawing Numbers** Packaging Specification Sales Drawing Test Summary

PK-44520-003-001 SD-44520-001-001 TS-44170-001-001

### This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L