

Glow-Wire Capable

## This document was generated on 01/27/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0449140801		
Status:	Active		1- for the second secon
Overview:	Micro-Fit Connector System		
Description:	Micro-Fit CPI Header, Compl	ant Pin Interface, Dual Row, Vertical, 8 Circuits, Tin (Sn)	
Plating, Glow-Wire Capable		No. of the second s	
	5, 1		and the second se
Documents:			
3D Model (PDF)		Test Summery TS 42045 001 001 (DDE)	
		<u>Test Summary TS-43045-001-001 (PDF)</u>	
Drawing (PDF)		Test Summary TS-43045-002-001 (PDF)	
<u>3D Model</u>		Test Summary TS-46235-001-001 (PDF)	
	<u>1 430450001-PS-KO-000 (PDF)</u>	Datasheet (PDF)	Series image - Reference only
	<u>h 430450001-PS-SP-000 (PDF)</u>	Symbol Footprint Data SYM-44914-0801-001 (PDF)	
Product Specification PS-43045-001 (PDF)		RoHS Certificate of Compliance (PDF)	EU ELV
Packaging Specifica	tion PK-70873-0314-001 (PDF)		Not Relevant
Agency Certification			EU RoHS China RoHS
CSA		LR19980	Compliant
UL		E29179	REACH SVHC
			Not Contained Per -
Application tooling part link			D(2021)4569-DC (8
Application Tooling F	Part Link	62203-0455	July 2021)
			Halogen-Free
General			Status
Product Family		PCB Headers	Low-Halogen
Series		<u>44914</u>	For more information, please visit <u>Contact US</u>
Application		Power, Wire-to-Board	For more mornation; please visit <u>contact co</u>
Comments		"""""""High Temperature Square Pin <p><p>This Molex</p></p>	China ROHS Green Image
		product is manufactured from material that has the	ELV Not Relevant
		following ratings, tested by independent agencies:.	RoHS Phthalates Not Contained
		a) A Glow Wire Ignition Temperature (GWIT) of at	,
		least 775 deg C per IEC 60695-2-13 b) A Glow	
		Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat	Search Parts in this Series
			44914 Series
			Mates With
		and fire. <p><p> The customers using this product</p></p>	430250800 Micro-Fit 3.0 Receptacle
		must determine its suitability for use in their particular	Housing
		application through testing or other acceptable means	
		as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product	Application Tooling   FAQ
			Tooling specifications and manuals are
		end-use standard(s). <p> If it is determined during</p>	found by selecting the products below.
		the customer's evaluation of suitability, that higher	Crimp Height Specifications are then
		performance is required, please contact Molex for	contained in the Application Tooling
		possible product options.""""""	Specification document.
Overview		Micro-Fit Connector System	Global
Product Name		Micro-Fit CPI	Description Product #
UPC		756054637678	Removal Tool <u>622030455</u>
Physical			
Physical		No	
Breakaway		No	
Circuits (Loaded)		8	
Circuits (maximum)		8 Diask	
Color - Resin		Black	
Durability (mating cy	cies max)	30	
Flammability Glow-Wire Capable		94V-0 Yes	

Yes

Material - Metal High Performance Alloy (HPA) Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin High Temperature Thermoplastic Net Weight 1.217/g Number of Rows 2 Orientation Vertical PCB Locator Yes PCB Retention Yes Packaging Type Tray Pitch - Mating Interface 3.00mm Plating min - Mating 5.080µm Plating min - Termination 5.080µm Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No Temperature Range - Operating -40° to +105°C Termination Interface: Style Through Hole - Compliant Pin Electrical Current - Maximum per Contact 8.5A Voltage - Maximum 600V Solder Process Data Lead-freeProcess Capability N/A **Material Info Reference - Drawing Numbers Packaging Specification** PK-70873-0314-001 **Product Specification** 430450001-PS-KO-000, 430450001-PS-SP-000, PS-43045-001 Sales Drawing SD-44914-002-001 Symbol/Footprint Data SYM-44914-0801-001 **Test Summary** TS-43045-001-001, TS-43045-002-001, TS-46235-001-001

## This document was generated on 01/27/2022 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707 

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN 

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000