

## This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:                                     | 0449141001  |  |   |
|--|---|--|---|
| Status:  | Active  |  | -   |
| Overview:  | Micro-Fit Connector System                            |  |   |
| Description:                                     |   | ant Pin Interface, Dual Row, Vertical, 10 Circuits, Tin (Sn)   |   |
| Docomption                                       | Plating, Glow-Wire Capable                            |  |   |
|  |   |  |   |
| Documents:                                       |   |  | The A   |
| <u>3D Model</u>                                  |   | Test Summary TS-43045-001-001 (PDF)  |   |
| <u>3D Model (PDF)</u>                            |   | Test Summary TS-43045-002-001 (PDF)  |   |
| Drawing (PDF)                                    |   | Test Summary TS-46235-001-001 (PDF)  | On the latence Defension and  |
|  | on 430450001-PS-KO-000 (PDF)                          | Datasheet (PDF)  | Series image - Reference only   |
|  | on 430450001-PS-SP-000 (PDF)<br>on PS-43045-001 (PDF) | Symbol Footprint Data SYM-44914-1001-001 (PDF)<br>RoHS Certificate of Compliance (PDF)                     |   |
|  | ation PK-70873-0314-001 (PDF)                         |  | EU ELV  |
|  |   |  | Not Relevant  |
| Agency Certificati                               | ion   |  | EU RoHS China RoHS  |
| CSA  |   | LR19980  | Compliant   |
| UL   |   | E29179   | REACH SVHC  |
| Application tooling port link                    |   |  | Not Contained Per -   |
| Application tooling part link         62200-8400 |   | 62200-8400   | D(2021)4569-DC (8<br>July 2021)   |
| Application Tooling                              |   | 62203-0455   | Halogen-Free  |
|  |   | Status   |   |
| General  |   |  | Low-Halogen   |
| Product Family<br>Series                         |   | PCB Headers<br>44914   | For more information, please visit Contact US                                 |
| Application                                      |   | Power, Wire-to-Board   | China ROHS Green Image  |
| Comments   |   | """"""High Temperature Square Pin <p><p>This Molex</p></p>   | ELV Not Relevant  |
|  |   | product is manufactured from material that has the   | RoHS Phthalates Not Contained   |
|  |   | following ratings, tested by independent agencies:.  |   |
|  |   | a) A Glow Wire Ignition Temperature (GWIT) of at   |   |
|  |   | least 775 deg C per IEC 60695-2-13 b) A Glow   | Search Parts in this Series   |
|  |   | Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the              | 44914 Series  |
|  |   | requirements set out in the International Standard IEC   |   |
|  |   | 60335-1 5th edition - household and similar electrical   | Mates With  |
|  |   | appliances - safety, section 30 Resistance to heat   | 430251000 Micro-Fit 3.0 Receptacle  |
|  |   | and fire. <p><p> The customers using this product</p></p>  | Housing   |
|  |   | must determine its suitability for use in their particular   |   |
|  |   | application through testing or other acceptable means  | Application Tooling   <u>FAQ</u>  |
|  |   | as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product | Tooling specifications and manuals are found by selecting the products below. |
|  |   | end-use standard(s). <p> If it is determined during</p>  | Crimp Height Specifications are then  |
|  |   | the customer's evaluation of suitability, that higher  | contained in the Application Tooling  |
|  |   | performance is required, please contact Molex for  | Specification document.   |
|  |   | possible product options.""""""  | Global  |
| Overview<br>Draduct Name                         |   | Micro-Fit Connector System   | Description Product #   |
| Product Name<br>UPC                              |   | Micro-Fit CPI<br>756054637685  | Compliant Pin <u>622008400</u>  |
|  |   | 100000001000   | Insertion Flat Rock   |
| Physical   |   |  | Removal Tool <u>622030455</u>   |
| Breakaway  |   | No   |   |
| Circuits (Loaded)                                |   | 10   |   |
| Circuits (maximum)<br>Color - Resin              |   | 10<br>Black  |   |
| Durability (mating c                             | cycles max)   | 30   |   |
| Flammability                                     | · · · · · · · · · · · · · · · · · · ·                 | 94V-0  |   |
| ı  |   |  |   |

**Glow-Wire Capable** Yes Material - Metal High Performance Alloy (HPA) Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin **High Temperature Thermoplastic** Net Weight 1.448/g Number of Rows 2 Orientation Vertical PCB Locator Yes **PCB** Retention Yes Packaging Type Tray Pitch - Mating Interface 3.00mm Plating min - Mating 5.080µm Plating min - Termination 5.080µm Polarized to PCB Yes Shrouded Fully Stackable No Surface Mount Compatible (SMC) No Temperature Range - Operating -40° to +105°C Termination Interface: Style Through Hole - Compliant Pin Electrical 8.5A Current - Maximum per Contact Voltage - Maximum 600V Solder Process Data Lead-freeProcess Capability N/A **Material Info Reference - Drawing Numbers** Packaging Specification PK-70873-0314-001 Product Specification 430450001-PS-KO-000, 430450001-PS-SP-000, PS-43045-001 Sales Drawing SD-44914-002-001 Symbol/Footprint Data SYM-44914-1001-001 **Test Summary** TS-43045-001-001, TS-43045-002-001, TS-46235-001-001

> This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707 

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN 

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000