

## This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0449150011</u>			
Status:	Active			
Overview: Magnetic and Mod		ular lacks/Plugs		
escription:		egory 6, Long Body, Shielded, 8/8, without Strain Relief	S S C IL	
	modular r rug, out		- 252 17	
Documents:				
3D Model		Product Specification PS-44915-003-001 (PDF)	L'UMPROV	
Drawing (PDF)		Packaging Specification PK-44915-003-001 (PDF)		
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)		
			_ ~	
Agency Certification	on		Series image - Reference only	
UL		E107635		
General			EU ELV	
Product Family		Modular Jacks/Plugs	Compliant	
Series		44915	EU RoHS China RoHS	
Component Type		Wire Plug		
		No	Compliant	
Magnetic			REACH SVHC	
Overview		Magnetic and Modular Jacks/Plugs	Not Contained Per -	
Performance Category		6	D(2021)4569-DC (8	
Power over Etherne	t (PoE)	N/A	July 2021)	
Product Name		Modular Plug 8/8, RJ45	Halogen-Free	
UPC		800756395555	Status	
			Low-Halogen	
Physical			For more information, please visit Contac	
Color - Resin		Clear	i el mere mermanon, piedes von <u>eemac</u>	
Durability (mating cycles max)		500	China ROHS Green Image	
Inverted / Top Latch		N/A	ELV Compliant	
Jack Height		N/A	RoHS Phthalates Not Contained	
Lightpipes/LEDs		None		
Material - Metal		Phosphor Bronze		
Material - Plating Mating		Gold		
Material - Plating Termination		Tin	Search Parts in this Series	
Material - Resin		Polycarbonate	44915 Series	
		•		
Net Weight		2.846/g	Mates With	
Orientation DCR L costor		N/A	FCC 68 Jacks	
PCB Locator		No		
PCB Retention		None		
Packaging Type		Bag	Application Tooling   FAQ	
Panel Mount		N/A	Tooling specifications and manuals are	
Pitch - Mating Interface		1.02mm	found by selecting the products below.	
Pitch - Termination Interface		1.02mm	Crimp Height Specifications are then	
Port Configuration		1x1	contained in the Application Tooling	
Positions / Loaded Contacts		8/8	Specification document.	
Temperature Range - Operating		-40° to +85°C	Global	
Termination Interface: Style		N/A	Description Product #	
Wire/Cable Type		Round	Hand Crimp Tool for <u>622020500</u>	
			RJ-45 CAT5, CAT5e,	
Electrical				
Current - Maximum per Contact		1.5A	CAT6, CAT6A Plugs,	
Grounding to Panel		N/A	22-28 AWG	
Shielded		Yes	ServiceGrade Hand <u>640160044</u>	
Voltage - Maximum		125V	Crimp Tool - Ratchet	
Solder Process Da		N1/A		
Lead-freeProcess C	apability	N/A		

**Reference - Drawing Numbers** Packaging Specification Product Specification Sales Drawing

PK-44915-003-001 PS-44915-003-001 SD-44915-001-001

## This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L