

This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

art Number:	0449150021			107356
Status:ActiveOverview:Magnetic and Model				\frown
				~ 1800
escription:	Modular Plug, Cate	gory 6, Long Body, Shielded, 8/8, with Strain Relief	13	14
				YE
Documents:			Start 1	
<u>3D Model</u>		Product Specification PS-44915-003-001 (PDF)		
<u>Drawing (PDF)</u>		Packaging Specification PK-44915-003-001 (PDF)		6
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	S.	
			- Series imag	e - Reference only
Agency Certification	1	E107635	Jeries Intag	
OL		E10/035	EU ELV	
General				
Product Family		Modular Jacks/Plugs	Compliant	
Series		44915	EU RoHS	China RoHS
Component Type		Wire Plug	Compliant	
Magnetic		No	REACH SVHC	
Overview		Magnetic and Modular Jacks/Plugs	Not Contained Per	
Performance Category		6		
Power over Ethernet (PoE)		o N/A	D(2021)4569-DC (8	1
Product Name			July 2021)	
		Modular Plug 8/8, RJ45	Halogen-Free	
UPC		800756395579	<u>Status</u>	
Dhysical			Low-Halogen	
Physical		Clear	For more information	on, please visit <u>Contac</u>
Color - Resin		Clear		a .
Durability (mating cycles max)		500	China ROHS	Green Image
Inverted / Top Latch		N/A	ELV	Compliant
Jack Height		N/A	RoHS Phthalates	Not Contained
Lightpipes/LEDs		None		
Material - Metal		Phosphor Bronze		
Material - Plating Mating		Gold	Cooreb Dorte in	this Corios
Material - Plating Termination		Tin	Search Parts in this Series	
Material - Resin		Polycarbonate	44915 Series	
Net Weight		3.062/g		
Orientation		N/A	Mates With	
PCB Locator		No	FCC 68 Jacks	
PCB Retention		None		
Packaging Type		Bag	Application Too	ling <u>FAQ</u>
Panel Mount		N/A		tions and manuals are
Pitch - Mating Interface		1.02mm		
Pitch - Termination Interface		1.02mm		g the products below.
Port Configuration		1x1		ecifications are then
Positions / Loaded Contacts		8/8		Application Tooling
			Specification doc	ument.
Temperature Range - Operating		-40° to +85°C	Global	_ • ···
Termination Interface: Style		N/A Downal	Description	Product #
Wire/Cable Type		Round	Hand Crimp Tool	
Electrical			RJ-45 CAT5, CA	
		1.5A	CAT6, CAT6A Pl	ugs,
Current - Maximum per Contact			22-28 AWG	
Grounding to Panel		N/A Vac	ServiceGrade Ha	nd <u>640160044</u>
Shielded Voltage - Maximum		Yes 125V	Crimp Tool - Ratchet	
-		12.3 V	,	
Solder Process Data		N/A		
Lead-freeProcess Ca	μαυπιτγ	IN/A		

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-44915-003-001 PS-44915-003-001 SD-44915-001-001

This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSGX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05 GSX-NS-88-3.05 GSX-NS2-88-3.05 GSX-NS-88-3.05-50 GSX-NS-88-3.05-50 GSX-NS-88-3.68 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 MRJR-5481-0F2 E5288-S000K3-L E5908-15A242-L