

This document was generated on 09/06/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 0451360601 | | | |
|----------------------------------------------|-------------------|---------------------------------------------|-----------------------------|------------------------------------|
| Status: | Active | | | and in the series |
| Overview: | Mega-Fit Power Co | opectors | | 13 |
| Description: | | | | 100 |
| Length, Matte Tin Plated, | | | | |
| | Longin, Mado Tini | | 100 100 | |
| Documents: | | | | 8 |
| 3D Model | | Datasheet (PDF) | | |
| 3D Model (PDF) | | RoHS Certificate of Compliance (PDF) | | |
| Drawing (PDF) | | | | |
| | | | Series imag | e - Reference only |
| General | | | | |
| Product Family | | Cable Assemblies | EU ELV | |
| Series | | <u>45136</u> | Not Relevant | |
| Application | | Power, Wire-to-Board | | |
| Assembly Configura | ation | Dual Ended Connectors | EU RoHS | China RoHS |
| Connector to Conne | ector | Mega-Fit-to-Mega-Fit | Compliant | |
| Overmolded | | No | REACH SVHC | |
| Overview | | Mega-Fit Power Connectors | Not Contained Per | |
| Product Name | | Mega-Fit | D(2021)4569-DC (8 | |
| Туре | | Discrete Wire Assembly, High-Power Assembly | July 2021) | |
| UPC | | 191128777858 | Halogen-Free | |
| | | | <u>Status</u> | |
| Physical | | | Not Low-Halogen | |
| Cable Length | | 150.00mm | For more information | on, please visit <u>Contact US</u> |
| Circuits (Loaded) | | 6 | | |
| Color - Resin | | Black | China ROHS | Green Image |
| Gender | | Female-Female | ELV | Not Relevant |
| Lock to Mating Part | | Yes | RoHS Phthalates | Not Contained |
| Material - Metal Copper Alloy | | | | |
| Material - Plating Mating | | Matte Tin | | |
| Material - Plating Termination | | Matte Tin | Search Parts in this Series | |
| Material - Resin | | Nylon | 45136 Series | |
| Net Weight | | 54.530/g | | |
| Number of Rows | | 2 | Mates With | |
| Packaging Type | | Bag | Mega-Fit Header | 76825 . 76829 |
| Pitch - Mating Interface | | 5.70mm | | , <u></u> |
| Plating min - Mating | | 1.524µm | | |
| Plating min - Termination | | 1.524µm | | |
| Single Ended Termination Interface: Style | | No Crime er Compression | | |
| Wire Insulation Diameter | | Crimp or Compression | | |
| Wire Size AWG | | 3.90mm 12 | | |
| Wire/Cable Type | | UL 1015 | | |
| | | | | |
| Electrical | | | | |
| Current - Maximum per Contact | | 23.0A | | |
| Voltage - Maximum | | 600V | | |
| Material Info | | | | |

Reference - Drawing Numbers Sales Drawing

451360601-000

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150