

## This document was generated on 09/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0451410310</u>			1 1/2 1/2
Status:	Active			
Overview:	MultiCat Power Conr	nectors with Precision-Machined Contacts	a dia dia dia dia dia dia dia dia dia di	- 1.4
Description:	MultiCat-to-MultiCat High-Power Off-the-Shelf (OTS) Cable Assembly, Female, Single Row, 1.0m Length, 8 AWG, 3 Circuits, Key A, Black		1000	79/
Decumenter				50
Documents: 3D Model		Detechant (DDE)		
		<u>Datasheet (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>	See. 19	
<u>3D Model (PDF)</u> <u>Drawing (PDF)</u>		KOHS Certificate of Compliance (PDP)		
<u>Drawing (FDF)</u>			Series image	e - Reference only
General				
Product Family		Cable Assemblies	EU ELV	
Series		<u>45141</u>	Not Relevant	
Application		Power, Wire-to-Board, Wire-to-Wire		
Assembly Configuration	on	Dual Ended Connectors	EU RoHS	<u>China RoHS</u>
Connector to Connect	or	MultiCat-to-MultiCat	Compliant with	
Overmolded		No	Exemption 6(c)	
Overview		MultiCat Power Connectors with Precision-Machined	REACH SVHC	
		Contacts	Contained Per -	
Product Name		MultiCat	D(2021)4569-DC (8	
Туре		Discrete Wire Assembly, High Reliability Assembly	July 2021)	
UPC		191128291590	Lead	
010		131120231000	Halogen-Free	
Physical			Status	
Cable Length		1.0m	Not Low-Halogen	
Circuits (Loaded)		3		n, please visit <u>Contact</u>
Color - Resin		Black		i, piedoe viole <u>oondoe</u>
Gender		Female-Female	China ROHS	50 Image
Lock to Mating Part		Yes	ELV	Not Relevant
Material - Metal		Copper Alloy	RoHS Phthalates	Not Contained
Material - Plating Mating		Gold over Nickel Phosphorus		
Material - Plating Terr		Gold		
Material - Resin		PEI		
			Search Parts in this Series	
Net Weight Number of Rows		333.500/g	45141 Series	
		I Dog		
Packaging Type		Bag	Mates With	
Pitch - Mating Interface		7.40mm	MultiCat High-Power Inline Plug Housing	
Plating min - Mating		0.100µm		tiCat High-Power Hea
Plating min - Termination		0.200µm	2018431030, 201	
Single Ended	0.1	No	<u> </u>	
Termination Interface:		Crimp or Compression		
Wire Insulation Diame	ter	4.03mm-5.84mm		
Wire Size AWG		8		
Wire/Cable Type		UL 10669		
Electrical		10.01		
Current - Maximum per Contact		40.0A		
Voltage - Maximum		1000V AC		
Material Info				
Engineering Number		KAB2540L1V01		
Reference - Drawing	Numbers			
Sales Drawing		451410301-000		

This document was generated on 09/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150