

## This document was generated on 09/09/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>)451410410</u>			
	Active			
		tors with Precision-Machined Contacts	and	- 19-42
		h-Power Off-the-Shelf (OTS) Cable Assembly, Female, Single	1.1-0	37///
		WG, 4 Circuits, Key A, Black	1.20100	
	g., e / .			
Documents:				
3D Model		Datasheet (PDF)	V. ()	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
<u>3D Model (PDF)</u>		<u></u>		
<u> </u>			Series image	e - Reference only
General				
Product Family		Cable Assemblies	EU ELV	
Series		<u>45141</u>	Not Relevant	
Application		Power, Wire-to-Board, Wire-to-Wire		
Assembly Configuration		Dual Ended Connectors	EU RoHS	<u>China RoHS</u>
Connector to Connector		MultiCat-to-MultiCat	Compliant with	
Overmolded		No	Exemption 6(c)	
Overview		MultiCat Power Connectors with Precision-Machined	REACH SVHC	
		Contacts	Contained Per -	
Product Name		MultiCat	D(2021)4569-DC (8	
Туре		Discrete Wire Assembly, High Reliability Assembly	July 2021)	
UPC		191128292450	Lead	
010		101120202400	Halogen-Free	
Physical			Status	
Cable Length		1.0m	Not Low-Halogen	
Circuits (Loaded)		4		n, please visit <u>Contact I</u>
Color - Resin		Black		i, ploade vien <u>eenader</u>
Gender		Female-Female	China ROHS	50 Image
Lock to Mating Part		Yes	ELV	Not Relevant
Material - Metal		Copper Alloy	RoHS Phthalates	Not Contained
Material - Plating Mating		Gold over Nickel Phosphorus	1	
Material - Plating Termin		Gold		
Material - Resin		PEI		
Net Weight		443.700/g	Search Parts in this Series	
Number of Rows		1	45141 Series	
Packaging Type		Bag		
Pitch - Mating Interface		7.40mm	Mates With	
Plating min - Mating		0.100µm	MultiCat High-Pow	er Inline Plug Housing
Plating min - Termination		0.200µm		tiCat High-Power Head
Single Ended		No	<u>2018431040</u> , <u>201</u>	
Termination Interface: St	wlo	Crimp or Compression	, <u> </u>	-
Wire Insulation Diameter		4.03mm-5.84mm		
Wire Size AWG				
Wire/Cable Type		8 UL 10669		
wire/Cable Type		OL 10009		
Electrical				
Current - Maximum per Contact		40.0A		
Voltage - Maximum		1000V AC		
Material Info				
Engineering Number		KAB2543L1V01		
Reference - Drawing N	umbers	454 449 494 999		
Sales Drawing		451410401-000		

This document was generated on 09/09/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150